

ODREY WALL 1.5

387320BB0


Project
Туре
Notes
Quantity
Date

GENERAL
Wall, Surface
Black Matt
RAL 9005 ^a
IP20
Interior
Indirect 0 lm
Direct 340 ^b to 350 ^c lm
Total 340 ^b to 350 ^c lm
CIE flux code: 94 98 100 100 73
LED
LED Lawren BARIA
Lamp PAR16
Lamp PAR16 Socket GU10
Lamp PAR16 Socket GU10 max. per socket 12.0 W
Lamp PAR16 Socket GU10
Lamp PAR16 Socket GU10 max. per socket 12.0 W CRI ≥ 90
Lamp PAR16 Socket GU10 max. per socket 12.0 W CRI ≥ 90 ELECTRICAL
Lamp PAR16 Socket GU10 max. per socket 12.0 W CRI ≥ 90 ELECTRICAL 100 - 240 V
Lamp PAR16 Socket GU10 max. per socket 12.0 W CRI ≥ 90

|--|



Wall surface luminaire made from die-cast aluminium; surface Black Matt wet painted; matt texture; RAL 9005; up or down light emission; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of $\,$ protection IP20; PC1; lamp not included;



Wall, Surface
Black Matt
RAL 9005 ^a
IP20
Interior
Indirect 0 lm
Direct 340 ^b to 350 ^c lm
Total 340 ^b to 350 ^c lm
CIE flux code: 94 98 100 100 73

L

Lamp PAR16
Socket GU10
max. per socket 12.0 W
CRI ≥ 90

Ε


100 - 240 V	
LED Inset 6.5 W	
Class 1	

PHYSICAL

Diameter 115 mm	
Height 245 mm	
0.36 kg	

^a Color may deviate slightly due to production conditions.

LIGHT DISTRIBUTION



May 9, 2024

 $^{^{\}mathrm{b}}$ PAR16 LAMP 2700K CRI90

 $^{^{\}mathrm{c}}$ PAR16 LAMP 3000K CRI90



ODREY WALL 1.5

387320BB0

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø⋅H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	ø50·60	901228B3
3000K >90 CRI GU10	Black	Ø50·60	901228B5
2700K >90 CRI GU10	White	Ø50·60	901228W3
3000K >90 CRI GU10	White	ø50·60	901228W5
2700K >80 CRI GU10	Silver	Ø50·60	90522782
3000K >80 CRI GU10	Silver	ø50·60	90522784