



PROJECT

TYPE

NOTES

QUANTITY

DATE



IP65



LUMINAIRE

Floor
Surface
Anthracite Grey
RAL 7016 ^a
IP65
Exterior
1350 lm

LED MODULE

3000 K
CRI ≥ 80
L80 / 60000 h
≤ 3 SDCM (initial MacAdam)

OPTICAL

Asymetric
CIE flux code: 61 91 99 100 100


ELECTRICAL

phase-cut dim
220 - 240 V
system 20.6 W
Class I

PHYSICAL


diameter 134 mm
height 30 mm
1.16 kg

LIGHT DISTRIBUTION



Floor surface mounted luminaire made from die-cast aluminium; surface Anthracite Grey; powder coated; matt texture; RAL 7016; direct light distribution; PCB 3-step binning; phase-cut dim; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 80; 220 - 240 V; degree of protection IP65; Class I; fixation base not included; driver included; inclusive 1300mm cable; light source not replaceable; control gear replaceable by end-user;

^a Colour may deviate slightly due to production conditions





Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.97	0.93	0.89	0.86	0.82
LSF	1	1	1	1	1

MF LMF × RSMF × LLMF × LSF

MF Maintenance Factor

LMF^a Luminaire Maintenance Factor

RSMF^a Room Surface Maintenance Factor

LLMF Lamp Lumens Maintenance Factor

LSF Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

BASE

POLE 170

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
with fixation plate	Anthracite Grey		160-91-170	910013A0
with fixation plate	Black		160-91-170	910013B0
with fixation plate	Bronze		160-91-170	910013Q0
with concrete ground fixation	Anthracite Grey		130-30-170	910073A0
with concrete ground fixation	Black		130-30-170	910073B0
with concrete ground fixation	Bronze		130-30-170	910073Q0

POLE 270

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
with fixation plate	Anthracite Grey		160-91-270	910014A0
with fixation plate	Black		160-91-270	910014B0
with fixation plate	Bronze		160-91-270	910014Q0
with concrete ground fixation	Anthracite Grey		130-30-270	910074A0
with concrete ground fixation	Black		130-30-270	910074B0
with concrete ground fixation	Bronze		130-30-270	910074Q0

POLE 470

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
with fixation plate	Anthracite Grey		160-91-470	910016A0
with fixation plate	Black		160-91-470	910016B0
with fixation plate	Bronze		160-91-470	910016Q0
with concrete ground fixation	Anthracite Grey		130-30-470	910076A0
with concrete ground fixation	Black		130-30-470	910076B0
with concrete ground fixation	Bronze		130-30-470	910076Q0

POLE 670

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
with fixation plate	Anthracite Grey		160-91-670	910018A0
with fixation plate	Black		160-91-670	910018B0
with fixation plate	Bronze		160-91-670	910018Q0
with concrete ground fixation	Anthracite Grey		130-30-670	910078A0
with concrete ground fixation	Black		130-30-670	910078B0
with concrete ground fixation	Bronze		130-30-670	910078Q0


POLE 870

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
with fixation plate	Anthracite Grey		160·91·870	910010A0
with fixation plate	Black		160·91·870	910010B0
with fixation plate	Bronze		160·91·870	910010Q0
with concrete ground fixation	Anthracite Grey		130·30·870	910070A0
with concrete ground fixation	Black		130·30·870	910070B0
with concrete ground fixation	Bronze		130·30·870	910070Q0