




**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_

**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



**LUMINAIRE**

Wall \_\_\_\_\_  
 Surface \_\_\_\_\_  
 Gold + White Matt \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_

**LAMP**

lamp PAR16 \_\_\_\_\_  
 socket GU10 \_\_\_\_\_  
 max. per socket 12.0 W \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_

**Electrical**

100 - 240 V \_\_\_\_\_  
 Class I \_\_\_\_\_  
 Standard \_\_\_\_\_

**Physical**



diameter 100 mm \_\_\_\_\_  
 height 170 mm \_\_\_\_\_  
 0.8 kg \_\_\_\_\_

**MEASURED LAMPS**

PAR16 LAMP 2700K CRI90 \_\_\_\_\_  
 480 lm \_\_\_\_\_  
 6.1 W \_\_\_\_\_

PAR16 LAMP 3000K CRI90 \_\_\_\_\_  
 495 lm \_\_\_\_\_  
 6 W \_\_\_\_\_

**LIGHT DISTRIBUTION**



['387120GWO'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



**ELECTRICAL ACCESSORIES**

**LED LAMPS**

Type	Colour	Voltage	Item number
	Black Texture		W901228B3
	Black Texture		W901228B5

**LAMPS**

**PAR16 LED Lamp**

Type	Colour	Voltage	Ø·H (MM)	Item number
2700K   >90 CRI   GU10	White		50-60	901228W3
3000K   >90 CRI   GU10	White		50-60	901228W5
2700K   >80 CRI   GU10	Silver		50-55	905227S2
3000K   >80 CRI   GU10	Silver		50-55	905227S4