

1.3

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium | steel

IP20 0.80kg

WW

GG

BB


GW

BG

GB

OPTIONAL

PAR16 6.5W GU10 phase-cut dim	
CODE	
2700K 460lm	901228W3
2700K 437lm	901228B3
3000K 500lm	901228W5
3000K 457lm	901228B5



1.4

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium | steel

IP20 0.34kg

387220WW0

387220GG0

387220BB0


387220GW0

387220BG0

387220GB0

OPTIONAL

PAR16 6.5W GU10 phase-cut dim	
CODE	
2700K 460lm	901228W3
2700K 437lm	901228B3
3000K 500lm	901228W5
3000K 457lm	901228B5



1.5

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium | steel

IP20 0.36kg

387320WW0

387320GG0

387320BB0

387320GW0

387320BG0

387320GB0

OPTIONAL

PAR16 6.5W GU10 phase-cut dim	
CODE	
2700K 460lm	901228W3
2700K 437lm	901228B3
3000K 500lm	901228W5
3000K 457lm	901228B5

ODREY

Wall surface



As awarded by The Chicago Athenaeum:
Museum of Architecture and Design

