




PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



Cylindrical wall surface mounted luminaire made from aluminium; surface Bronze; wet painted; brushed; RAL 7013; direct light distribution; PCB 3-step binning; phase-cut dim; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 1; inclusive flaps for adjustable beam angle; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

LUMINAIRE

Wall _____
 Surface _____
 Bronze _____
 RAL 7013 ^a _____
 IP20 _____
 Interior _____
 370 lm _____

LED Module

3000 K _____
 CRI ≥ 90 _____
 ≤ 3 SDCM (initial MacAdam) _____
 440 lm _____
 73 lm/W ^b _____

Optical

Variable _____


Electrical

phase-cut dim _____
 220 - 240 V _____
 system 6.0 W _____
 Class I _____

Physical

diameter 150 mm _____
 height 100 mm _____
 0.62 kg _____

^a Colour may deviate slightly due to production conditions
^b Without electrical and optical losses



[‘342168Q5’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.97	0.93	0.89	0.85	0.81
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.