




PROJECT

TYPE


NOTES

QUANTITY

DATE



Cylindrical wall surface mounted luminaire made from aluminium; surface Bronze; wet painted; brushed; RAL 7013; direct light distribution; PCB 3-step binning; phase-cut dim; light colour 2700 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 1; inclusive flaps for adjustable beam angle; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Wall
Surface
Bronze
RAL 7013 ^a
IP20
Interior
350 lm

LED Module

2700 K
CRI ≥ 90
L80 / 55000h
 ≤ 3 SDCM (initial MacAdam)
400 lm
67 lm/W ^b

Optical

Variable

Electrical

phase-cut dim
220 - 240 V
system 6.0 W
Class I

Physical

diameter 150 mm
height 100 mm
0.62 kg

^a Colour may deviate slightly due to production conditions
^b Without electrical and optical losses



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.97	0.93	0.89	0.85	0.81
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.