



**PROJECT**

**TYPE**


**NOTES**

**QUANTITY**

**DATE**



Cylindrical wall surface mounted luminaire made from aluminium; surface Copper; wet painted; brushed; direct light distribution; PCB 3-step binning; phase-cut dim; light colour 3000 K;  $\leq 3$  SDCM (initial MacAdam); CRI  $\geq 90$ ; 220 - 240 V; degree of protection IP20; Class I; inclusive flaps for adjustable beam angle; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



**LUMINAIRE**

Wall  
Surface  
Copper  
IP20  
Interior  
370 lm

**LED Module**

3000 K  
CRI  $\geq 90$   
L80 / 55000h  
 $\leq 3$  SDCM (initial MacAdam)  
440 lm  
73 lm/W<sup>a</sup>

**Optical**

Variable

**Electrical**

phase-cut dim  
220 - 240 V  
system 6.0 W  
Class I

**Physical**

diameter 150 mm  
height 100 mm  
0.62 kg

<sup>a</sup> Without electrical and optical losses



## Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.97	0.93	0.89	0.85	0.81
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

<sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.