

Project _____

Type _____

Notes _____

Quantity _____

Date _____

GENERAL

Ceiling , Suspended
Black Matt + Gold
IP20
Interior
Output: 450^a, 470^b lm
CIE flux code: 94 98 100 100 98

LED

Lamp PAR16
Socket GU10
max. per socket 12.0 W
CRI ≥ 90

ELECTRICAL

100 - 240 V
LED Inset 6.5 W
Class 1

PHYSICAL


Diameter 191 mm
Height 150 mm
0.75 kg

^a PAR16 LAMP 2700K CRI90


^b PAR16 LAMP 3000K CRI90



Ceiling suspended luminaire made from aluminium; surface Black Matt + Gold wet painted; matt texture; inclusive adjustable cable suspension max. 4000mm in Signal Black; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; PC1; ceiling base not included;



LIGHT DISTRIBUTION



LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	Ø50-60	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	Ø50-60	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	Ø50-60	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	Ø50-60	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	Ø50-60	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	Ø50-60	9 0 5 2 2 7 S 4

SINGLE SUSPENSION

Invisible ceiling base

COLOUR	L · W (MM)	ORDERCODE
Black	140-66	9 0 0 1 5 1 9 5
White	140-66	9 0 0 1 5 1 9 6



Single base

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
ceiling base round	Black	Ø84-29	9 0 0 5 2 0 2 1
ceiling base round	White	Ø84-29	9 0 0 5 2 0 2 2

Semi recessed base

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
for shades without steel wire only	White	Ø84-72	9 0 0 5 2 0 2 6
for shades without steel wire only	Black	Ø84-72	9 0 0 5 2 0 2 7

WALL BASE

WALL BASE

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
for 1 luminaire	White	Ø82-32	9 0 0 1 9 1 9 5
for 1 luminaire	Black	Ø82-32	9 0 0 1 9 1 9 6

Cable Wall-Ceiling Bracket

COLOUR	Ø · H (MM)	ORDERCODE
White	Ø16-30	9 0 0 1 9 1 9 7
Black	Ø16-30	9 0 0 1 9 1 9 8

WEVER & DUCRÉ
LIGHTING

ODREY
1.6

287620BG0

MULTI SUSPENSION

Multiple base round

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
up to max. 4 luminaires	White	Ø123·44	9 0 0 5 2 0 0 5
up to max. 4 luminaires	Black	Ø123·44	9 0 0 5 2 0 0 6
up to max. 8 luminaires	White	Ø123·44	9 0 0 5 2 0 3 1
up to max. 8 luminaires	Black	Ø123·44	9 0 0 5 2 0 3 2

Multiple base linear

TYPE	COLOUR	L·W·H (MM)	ORDERCODE
up to max. 2 luminaires	White	600·30·45	9 0 0 5 2 0 0 7
up to max. 2 luminaires	Black	600·30·45	9 0 0 5 2 0 0 8
up to max. 3 luminaires	White	900·30·45	9 0 0 5 2 0 0 9
up to max. 3 luminaires	Black	900·30·45	9 0 0 5 2 0 1 0
up to max. 4 luminaires	White	1200·30·45	9 0 0 5 2 0 1 1
up to max. 4 luminaires	Black	1200·30·45	9 0 0 5 2 0 1 2
up to max. 5 luminaires	White	1500·30·45	9 0 0 5 2 0 1 3
up to max. 5 luminaires	Black	1500·30·45	9 0 0 5 2 0 1 4

OPTIONAL

Hook

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
standard multi suspension hook	Black	Ø3·83	9 0 0 5 2 0 2 4
standard multi suspension hook	White	Ø3·83	9 0 0 5 2 0 2 5
optional multi suspension hook	Black	Ø5·90	9 0 0 5 2 0 6 5
optional multi suspension hook	White	Ø5·90	9 0 0 5 2 0 6 6
for cable 4.25-5.5mm diameter	White	Ø15·35	9 0 0 5 2 0 7 9
for cable 4.25-5.5mm diameter	Black	Ø15·35	9 0 0 5 2 0 8 0

Inner cover

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
suitable for ODREY 1.6 1.7	Black	Ø55·42	9 1 1 4 2 0 B 0
suitable for ODREY 1.6 1.7	Gold	Ø55·42	9 1 1 4 2 0 G 0
suitable for ODREY 1.6 1.7	White	Ø55·42	9 1 1 4 2 0 W 0

[‘287620BG0’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com