

Project \_\_\_\_\_

Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantity \_\_\_\_\_

Date \_\_\_\_\_

#### GENERAL

Ceiling , Suspended  
Black Matt + Gold  
IP20  
Interior  
Output: 350<sup>a</sup>, 365<sup>b</sup> lm  
CIE flux code: 94 98 100 100 76

#### LED

Lamp PAR16  
Socket GU10  
max. per socket 12.0 W  
CRI ≥ 90

#### ELECTRICAL

100 - 240 V  
LED Inset 6.5 W  
Class 1

#### PHYSICAL


Diameter 115 mm  
Height 235 mm  
0.9 kg

<sup>a</sup> PAR16 LAMP 2700K CRI90


<sup>b</sup> PAR16 LAMP 3000K CRI90



Ceiling suspended luminaire made from aluminium; surface Black Matt + Gold wet painted; matt texture; inclusive adjustable cable suspension max. 4000mm in Signal Black; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; PC1; ceiling base not included;



#### LIGHT DISTRIBUTION



LAMPS

PAR16 LED Lamp

| TYPE                   | COLOUR | Ø · H (MM) | ORDERCODE       |
|------------------------|--------|------------|-----------------|
| 2700K   >90 CRI   GU10 | Black  | Ø50-60     | 9 0 1 2 2 8 B 3 |
| 3000K   >90 CRI   GU10 | Black  | Ø50-60     | 9 0 1 2 2 8 B 5 |
| 2700K   >90 CRI   GU10 | White  | Ø50-60     | 9 0 1 2 2 8 W 3 |
| 3000K   >90 CRI   GU10 | White  | Ø50-60     | 9 0 1 2 2 8 W 5 |
| 2700K   >80 CRI   GU10 | Silver | Ø50-60     | 9 0 5 2 2 7 S 2 |
| 3000K   >80 CRI   GU10 | Silver | Ø50-60     | 9 0 5 2 2 7 S 4 |

SINGLE SUSPENSION

Invisible ceiling base

| COLOUR | L · W (MM) | ORDERCODE       |
|--------|------------|-----------------|
| Black  | 140-66     | 9 0 0 1 5 1 9 5 |
| White  | 140-66     | 9 0 0 1 5 1 9 6 |



Single base

| TYPE               | COLOUR | Ø · H (MM) | ORDERCODE       |
|--------------------|--------|------------|-----------------|
| ceiling base round | Black  | Ø84-29     | 9 0 0 5 2 0 2 1 |
| ceiling base round | White  | Ø84-29     | 9 0 0 5 2 0 2 2 |

Semi recessed base

| TYPE                               | COLOUR | Ø · H (MM) | ORDERCODE       |
|------------------------------------|--------|------------|-----------------|
| for shades without steel wire only | White  | Ø84-72     | 9 0 0 5 2 0 2 6 |
| for shades without steel wire only | Black  | Ø84-72     | 9 0 0 5 2 0 2 7 |

WALL BASE

WALL BASE

| TYPE            | COLOUR | Ø · H (MM) | ORDERCODE       |
|-----------------|--------|------------|-----------------|
| for 1 luminaire | White  | Ø82-32     | 9 0 0 1 9 1 9 5 |
| for 1 luminaire | Black  | Ø82-32     | 9 0 0 1 9 1 9 6 |

Cable Wall-Ceiling Bracket

| COLOUR | Ø · H (MM) | ORDERCODE       |
|--------|------------|-----------------|
| White  | Ø16-30     | 9 0 0 1 9 1 9 7 |
| Black  | Ø16-30     | 9 0 0 1 9 1 9 8 |

MULTI SUSPENSION

Multiple base round

| TYPE                    | COLOUR | Ø·H (MM) | ORDERCODE       |
|-------------------------|--------|----------|-----------------|
| up to max. 4 luminaires | White  | Ø123·44  | 9 0 0 5 2 0 0 5 |
| up to max. 4 luminaires | Black  | Ø123·44  | 9 0 0 5 2 0 0 6 |
| up to max. 8 luminaires | White  | Ø123·44  | 9 0 0 5 2 0 3 1 |
| up to max. 8 luminaires | Black  | Ø123·44  | 9 0 0 5 2 0 3 2 |

Multiple base linear

| TYPE                    | COLOUR | L·W·H (MM) | ORDERCODE       |
|-------------------------|--------|------------|-----------------|
| up to max. 2 luminaires | White  | 600·30·45  | 9 0 0 5 2 0 0 7 |
| up to max. 2 luminaires | Black  | 600·30·45  | 9 0 0 5 2 0 0 8 |
| up to max. 3 luminaires | White  | 900·30·45  | 9 0 0 5 2 0 0 9 |
| up to max. 3 luminaires | Black  | 900·30·45  | 9 0 0 5 2 0 1 0 |
| up to max. 4 luminaires | White  | 1200·30·45 | 9 0 0 5 2 0 1 1 |
| up to max. 4 luminaires | Black  | 1200·30·45 | 9 0 0 5 2 0 1 2 |
| up to max. 5 luminaires | White  | 1500·30·45 | 9 0 0 5 2 0 1 3 |
| up to max. 5 luminaires | Black  | 1500·30·45 | 9 0 0 5 2 0 1 4 |

OPTIONAL

Hook

| TYPE                           | COLOUR | Ø·H (MM) | ORDERCODE       |
|--------------------------------|--------|----------|-----------------|
| standard multi suspension hook | Black  | Ø3·83    | 9 0 0 5 2 0 2 4 |
| standard multi suspension hook | White  | Ø3·83    | 9 0 0 5 2 0 2 5 |
| optional multi suspension hook | Black  | Ø5·90    | 9 0 0 5 2 0 6 5 |
| optional multi suspension hook | White  | Ø5·90    | 9 0 0 5 2 0 6 6 |
| for cable 4.25-5.5mm diameter  | White  | Ø15·35   | 9 0 0 5 2 0 7 9 |
| for cable 4.25-5.5mm diameter  | Black  | Ø15·35   | 9 0 0 5 2 0 8 0 |