

Project _____

Type _____

Notes _____

Quantity _____

Date _____

GENERAL

Ceiling , Suspended _____

White Matt _____

IP20 _____

Interior _____

Output: 460^a, 500^b lm _____

CIE flux code: 94 98 100 100 91 _____

LED

Lamp PAR16 _____

Socket GU10 _____

max. per socket 12.0 W _____

CRI ≥ 90 _____

ELECTRICAL

100 - 240 V _____

LED Inset 6.5 W _____

Class 1 _____

PHYSICAL

Diameter 100 mm _____

Height 160 mm _____


0.26 kg _____

^a PAR16 LAMP 2700K CRI90


^b PAR16 LAMP 3000K CRI90



Ceiling suspended luminaire made from aluminium; surface White Matt wet painted; matt texture; inclusive adjustable cable suspension max. 4000mm in Pure White; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; PC1; ceiling base not included;



LIGHT DISTRIBUTION



LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	Ø50·60	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	Ø50·60	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	Ø50·60	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	Ø50·60	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	Ø50·60	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	Ø50·60	9 0 5 2 2 7 S 4

SINGLE SUSPENSION

Invisible ceiling base

COLOUR	L · W (MM)	ORDERCODE
Black	140·66	9 0 0 1 5 1 9 5
White	140·66	9 0 0 1 5 1 9 6



Single base

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
ceiling base round	Black	Ø84·29	9 0 0 5 2 0 2 1
ceiling base round	White	Ø84·29	9 0 0 5 2 0 2 2

Semi recessed base

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
for shades without steel wire only	White	Ø84·72	9 0 0 5 2 0 2 6
for shades without steel wire only	Black	Ø84·72	9 0 0 5 2 0 2 7

WALL BASE

WALL BASE

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
for 1 luminaire	White	Ø82·32	9 0 0 1 9 1 9 5
for 1 luminaire	Black	Ø82·32	9 0 0 1 9 1 9 6

Cable Wall-Ceiling Bracket

COLOUR	Ø · H (MM)	ORDERCODE
White	Ø16·30	9 0 0 1 9 1 9 7
Black	Ø16·30	9 0 0 1 9 1 9 8

MULTI SUSPENSION

Multiple base round

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
up to max. 4 luminaires	White	Ø123 · 44	9 0 0 5 2 0 0 5
up to max. 4 luminaires	Black	Ø123 · 44	9 0 0 5 2 0 0 6
up to max. 8 luminaires	White	Ø123 · 44	9 0 0 5 2 0 3 1
up to max. 8 luminaires	Black	Ø123 · 44	9 0 0 5 2 0 3 2

Multiple base linear

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
up to max. 2 luminaires	White	600 · 30 · 45	9 0 0 5 2 0 0 7
up to max. 2 luminaires	Black	600 · 30 · 45	9 0 0 5 2 0 0 8
up to max. 3 luminaires	White	900 · 30 · 45	9 0 0 5 2 0 0 9
up to max. 3 luminaires	Black	900 · 30 · 45	9 0 0 5 2 0 1 0
up to max. 4 luminaires	White	1200 · 30 · 45	9 0 0 5 2 0 1 1
up to max. 4 luminaires	Black	1200 · 30 · 45	9 0 0 5 2 0 1 2
up to max. 5 luminaires	White	1500 · 30 · 45	9 0 0 5 2 0 1 3
up to max. 5 luminaires	Black	1500 · 30 · 45	9 0 0 5 2 0 1 4

OPTIONAL

Hook

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
standard multi suspension hook	Black	Ø3 · 83	9 0 0 5 2 0 2 4
standard multi suspension hook	White	Ø3 · 83	9 0 0 5 2 0 2 5
optional multi suspension hook	Black	Ø5 · 90	9 0 0 5 2 0 6 5
optional multi suspension hook	White	Ø5 · 90	9 0 0 5 2 0 6 6
for cable 4.25-5.5mm diameter	White	Ø15 · 35	9 0 0 5 2 0 7 9
for cable 4.25-5.5mm diameter	Black	Ø15 · 35	9 0 0 5 2 0 8 0