



WEVER & DUCRÉ
LIGHTING

ODREY on STREX 1.2 LED

187265GB5

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling , Track Suspended

Gold + Black Matt

IP20

Interior

Output: 430 lm

CIE flux code: 95 97 99 100 100

LED

3000 K

CRI ≥ 90

L70 / 55000h

2 SDCM

OPTICAL

Medium , Beam angle 32°

ELECTRICAL

DALI-2

48 V

LED Inset 7.0 W

Class 3

PHYSICAL

Diameter 250 mm

Height 119 mm


0.48 kg

175 (adapter) mm


incl. Strex 48 V track adapter



Suspended luminaire for 48V tracks made from die-cast aluminium; track adapter with height adjustable cable system; surface Gold + Black Matt wet painted; matt texture; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; 48 V; degree of protection IP20; PC3; light source replaceable by an authorized professional;



LIGHT DISTRIBUTION



ODREY

on STREX 1.2 LED

187265GB5

CONE DIAGRAM

medium 32°

h (m)	E0° (lx)	ø (m)
1	1230	0.57
2	310	1.15
3	140	1.72
4	80	2.29
5	50	2.87

ELECTRICAL

In Track Driver 100W

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface	Black	438-16-18	9 0 0 1 4 1 4 3
STREX system surface	White	438-16-18	9 0 0 1 4 1 4 4
STREX system suspended	White	3000	9 0 0 1 4 1 5 7
STREX system suspended	Black	3000	9 0 0 1 4 1 7 4
STREX system surface	Black	468-26-29	9 0 0 1 4 1 7 6
STREX system surface	White	468-26-29	9 0 0 1 4 1 7 8
STREX system surface	Bronze + Black	468-26-29	9 0 0 1 4 3 7 6
STREX system surface	Champagne + Black	468-26-29	9 0 0 1 4 3 7 8

In Track Driver 250W

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface	Black	408-16-18	9 0 0 1 4 1 4 5
STREX system surface	White	408-16-18	9 0 0 1 4 1 4 6
STREX system suspended	White	3000	9 0 0 1 4 1 5 8
STREX system suspended	Black	3000	9 0 0 1 4 1 7 5
STREX system surface	Black	438-26-29	9 0 0 1 4 1 7 7
STREX system surface	White	438-26-29	9 0 0 1 4 1 7 9
STREX system surface	Bronze + Black	438-26-29	9 0 0 1 4 3 7 7
STREX system surface	Champagne + Black	438-26-29	9 0 0 1 4 3 7 9

Power Feed

TYPE	COLOUR	L · H (MM)	ORDERCODE
STREX system	White	112-18	9 0 0 1 4 1 5 3
STREX system	Black	112-18	9 0 0 1 4 1 5 4

Connector

TYPE	COLOUR	L · H (MM)	ORDERCODE
STREX system	White	105-18	9 0 0 1 4 1 9 6
STREX system	Black	105-18	9 0 0 1 4 1 9 7

ODREY

on STREX 1.2 LED

187265GB5

L-Connector

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface/suspended	White	105-105-19	9 0 0 1 4 1 9 8
STREX system surface/suspended	Black	105-105-19	9 0 0 1 4 1 9 9
STREX system recessed	White	105-105-19	9 0 0 1 4 2 5 1
STREX system recessed	Black	105-105-19	9 0 0 1 4 2 5 2
STREX system surface/suspended	Champagne + Black	105-105-19	9 0 0 1 4 3 9 8
STREX system surface/suspended	Bronze + Black	105-105-19	9 0 0 1 4 3 9 9

T-Connector

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface	White	275-146-18	9 0 0 1 4 2 9 2
STREX system surface	Black	275-146-18	9 0 0 1 4 2 9 3

X-Connector

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface	Black	275-275-18	9 0 0 1 4 2 9 4
STREX system surface	White	275-275-18	9 0 0 1 4 2 9 5

In Line Driver 100W

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system suspended	White	439-26-44	9 0 0 1 4 3 6 0
STREX system suspended	Black	439-26-44	9 0 0 1 4 3 6 1
STREX system surface	White	439-26-44	9 0 0 1 4 3 6 6
STREX system surface	Black	439-26-44	9 0 0 1 4 3 6 7

In Line Driver 150W

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system suspended	White	439-26-44	9 0 0 1 4 3 6 2
STREX system suspended	Black	439-26-44	9 0 0 1 4 3 6 3
STREX system surface	White	439-26-44	9 0 0 1 4 3 7 0
STREX system surface	Black	439-26-44	9 0 0 1 4 3 7 1

Ceiling Driver 100W

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system suspended	White	439-26-44	9 0 0 1 4 3 6 8
STREX system suspended	Black	439-26-44	9 0 0 1 4 3 6 9

Ceiling Driver 150W

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system suspended	White	439-26-44	9 0 0 1 4 3 7 2
STREX system suspended	Black	439-26-44	9 0 0 1 4 3 7 3

DALI Selv Device

TYPE	L · W · H (MM)	ORDERCODE
STREX system	213-37-25	9 0 0 1 9 1 9 3



ODREY

on STREX 1.2 LED

187265GB5

Driver

TYPE	L · W · H (MM)	ORDERCODE
STREX system 100W	350-30-18	9 0 2 1 8 9 0 1
STREX system 150W	350-30-18	9 0 2 1 8 9 0 2
STREX system 250W	400-40-22	9 0 2 1 8 9 0 3

SUSPENDED

Track Profile 2m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system suspended indirect light	Black	2000-26-29	9 0 0 1 4 0 B 5
STREX system custom cut suspended indirect light	Black	1000-1999-26-29	9 0 0 1 4 0 B 5 C C
STREX system suspended indirect light	White	2000-26-29	9 0 0 1 4 0 W 5
STREX system custom cut suspended indirect light	White	1000-1999-26-29	9 0 0 1 4 0 W 5 C C

Suspension Set

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system 1.5m suspended	Stainless Steel	80-23-1500	9 0 0 1 4 1 6 0
STREX system 3.0m suspended	Stainless Steel	80-23-3000	9 0 0 1 4 1 6 1
STREX system 1.5m suspended	Black	80-23-1500	9 0 0 1 4 2 7 4
STREX system 3.0m suspended	Black	80-23-3000	9 0 0 1 4 2 7 5

Track Profile 3m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system suspended indirect light	Black	3000-26-29	9 0 0 1 4 1 B 5
STREX system custom cut suspended indirect light	Black	2001-2999-26-29	9 0 0 1 4 1 B 5 C C
STREX system suspended indirect light	White	3000-26-29	9 0 0 1 4 1 W 5
STREX system custom cut suspended indirect light	White	2001-2999-26-29	9 0 0 1 4 1 W 5 C C

COVER

Blank Cover 2m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system	Black	2000-18-3	9 1 1 0 0 2 B 0
STREX system	White	2000-18-3	9 1 1 0 0 2 W 0

RECESSED

End Cap

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system recessed	White	37-10-27	9 0 0 1 4 1 4 9
STREX system recessed	Black	37-10-27	9 0 0 1 4 1 5 0

ODREY

on STREX 1.2 LED

187265GB5

Track Profile 1m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system recessed	White	1000-37-33	9 0 0 1 4 1 8 7
STREX system custom cut recessed	White	200-999-37-33	9 0 0 1 4 1 8 7 C C
STREX system recessed	Black	1000-37-33	9 0 0 1 4 1 8 8
STREX system custom cut recessed	Black	200-999-37-33	9 0 0 1 4 1 8 8 C C

Track Profile 2m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system recessed	White	2000-37-33	9 0 0 1 4 1 8 9
STREX system custom cut recessed	White	1001-1999-37-33	9 0 0 1 4 1 8 9 C C
STREX system recessed	Black	2000-37-33	9 0 0 1 4 1 9 0
STREX system custom cut recessed	Black	1001-1999-37-33	9 0 0 1 4 1 9 0 C C

Track Profile 3m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system recessed	White	3000-37-33	9 0 0 1 4 1 9 1
STREX system custom cut recessed	White	2001-2999-37-33	9 0 0 1 4 1 9 1 C C
STREX system recessed	Black	3000-37-33	9 0 0 1 4 1 9 2
STREX system custom cut recessed	Black	2001-2999-37-33	9 0 0 1 4 1 9 2 C C

Mounting Bracket

TYPE	ORDERCODE
STREX system recessed	9 0 0 1 4 1 9 3

L-Connector non-electrical

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system recessed	White	105-105-19	9 0 0 1 4 2 5 6
STREX system recessed	Black	105-105-19	9 0 0 1 4 2 5 7

SURFACE

End Cap

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface/suspended	White	26-2.5-29	9 0 0 1 4 1 4 7
STREX system surface/suspended	Black	26-2.5-29	9 0 0 1 4 1 4 8
STREX system surface/suspended	Champagne	26-2.5-29	9 0 0 1 4 3 4 7
STREX system surface/suspended	Bronze	26-2.5-29	9 0 0 1 4 3 4 8

Track Profile 1m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface/suspended	White	1000-26-29	9 0 0 1 4 1 8 1
STREX system custom cut surface/suspended	White	200-999-26-29	9 0 0 1 4 1 8 1 C C
STREX system surface/suspended	Black	1000-26-29	9 0 0 1 4 1 8 2
STREX system custom cut surface/suspended	Black	200-999-26-29	9 0 0 1 4 1 8 2 C C



WEVER & DUCRÉ
LIGHTING

ODREY

on STREX 1.2 LED

187265GB5

Track Profile 2m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface/suspended	White	2000-26-29	9 0 0 1 4 1 8 3
STREX system custom cut surface/suspended	White	1001-1999-26-29	9 0 0 1 4 1 8 3 C C
STREX system surface/suspended	Black	2000-26-29	9 0 0 1 4 1 8 4
STREX system custom cut surface/suspended	Black	1001-1999-26-29	9 0 0 1 4 1 8 4 C C
STREX system surface/suspended	Champagne	2000-26-29	9 0 0 1 4 3 8 3
STREX system custom cut surface/suspended	Champagne	1001-1999-26-29	9 0 0 1 4 3 8 3 C C
STREX system surface/suspended	Bronze	2000-26-29	9 0 0 1 4 3 8 4
STREX system custom cut surface/suspended	Bronze	1001-1999-26-29	9 0 0 1 4 3 8 4 C C

Track Profile 3m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface/suspended	White	3000-26-29	9 0 0 1 4 1 8 5
STREX system custom cut surface/suspended	White	2001-2999-26-29	9 0 0 1 4 1 8 5 C C
STREX system surface/suspended	Black	3000-26-29	9 0 0 1 4 1 8 6
STREX system custom cut surface/suspended	Black	2001-2999-26-29	9 0 0 1 4 1 8 6 C C
STREX system surface/suspended	Champagne	3000-26-29	9 0 0 1 4 3 8 5
STREX system custom cut surface/suspended	Champagne	2001-2999-26-29	9 0 0 1 4 3 8 5 C C
STREX system surface/suspended	Bronze	3000-26-29	9 0 0 1 4 3 8 6
STREX system custom cut surface/suspended	Bronze	2001-2999-26-29	9 0 0 1 4 3 8 6 C C

L-Connector non-electrical

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface	White	105-105-19	9 0 0 1 4 2 5 8
STREX system surface	Black	105-105-19	9 0 0 1 4 2 5 9
STREX system surface	Gold + Black	105-105-19	9 0 0 1 4 4 5 8
STREX system surface	Bronze + Black	105-105-19	9 0 0 1 4 4 5 9