



WEVER & DUCRÉ
LIGHTING

ODREY on track 1.7 PAR16

187720GG0

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling , Track Suspended

Gold

IP20

Interior

Output: 460^a, 480^b lm

CIE flux code: 94 98 100 100 100

LED

Lamp PAR16

Socket GU10

max. per socket 12.0 W

CRI ≥ 90

ELECTRICAL

incl. 1-phase Global track adapter

100 - 240 V

LED Inset 6.5 W

Class 1

PHYSICAL

Diameter 151 mm

Height 125 mm

0.32 kg

75 (adapter) mm


incl. 1-phase track adapter

^a PAR16 LAMP 2700K CRI90


^b PAR16 LAMP 3000K CRI90



Suspended luminaire for 1-phase tracks made from die-cast aluminium; track adapter with height adjustable cable system; surface Gold wet painted; matt texture; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; PC1; lamp not included;



LIGHT DISTRIBUTION



ODREY

on track 1.7 PAR16

187720GG0

OPTIONAL

Inner cover

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
suitable for ODREY 1.6 1.7	Black	Ø55·42	9 1 1 4 2 0 B 0
suitable for ODREY 1.6 1.7	Gold	Ø55·42	9 1 1 4 2 0 G 0
suitable for ODREY 1.6 1.7	White	Ø55·42	9 1 1 4 2 0 W 0

SUSPENDED

Track Adapter 1.0

TYPE	COLOUR	L · H (MM)	ORDERCODE
1-phase track	Black	85·45	9 0 0 1 4 0 4 3
1-phase track	White	85·45	9 0 0 1 4 0 4 4

Suspension Set 1.5m

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
1-phase track suspended	White	Ø29·1500	9 0 0 1 4 1 0 1
1-phase track suspended	Black	Ø29·1500	9 0 0 1 4 1 0 2

Suspension Set 3.0m

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
1-phase track suspended	White	Ø29·3000	9 0 0 1 4 1 0 3
1-phase track suspended	Black	Ø29·3000	9 0 0 1 4 1 0 4

Track Adapter 2.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	80·24·26	9 0 0 1 4 2 7 7
1-phase track	Black	80·24·26	9 0 0 1 4 2 7 8

CORNER

Adjustable Corner

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	Black	81·81·20	9 0 0 1 4 0 4 1
1-phase track	White	81·81·20	9 0 0 1 4 0 4 2

RECESSED

Mounting Bracket

TYPE	L · W · H (MM)	ORDERCODE
1-phase track recessed	35·59·35	9 0 0 1 4 1 0 0

ODREY

on track 1.7 PAR16

187720GG0

Track Profile 1m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track recessed	White	1000-50-20	9 0 0 1 4 1 1 8
1-phase track recessed	Black	1000-50-20	9 0 0 1 4 1 1 9

Track Profile 2m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track recessed	White	2000-50-20	9 0 0 1 4 1 2 0
1-phase track recessed	Black	2000-50-20	9 0 0 1 4 1 2 1

Track Profile 3m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track recessed	White	3000-50-20	9 0 0 1 4 1 2 2
1-phase track recessed	Black	3000-50-20	9 0 0 1 4 1 2 3

Coverplate End Feed

TYPE	COLOUR	L · W (MM)	ORDERCODE
1-phase track recessed	White	75-50	9 0 0 1 4 1 2 4
1-phase track recessed	Black	75-50	9 0 0 1 4 1 2 5

Coverplate I/L/T/X

TYPE	COLOUR	L · W (MM)	ORDERCODE
1-phase track recessed	White	100-100	9 0 0 1 4 1 2 6
1-phase track recessed	Black	100-100	9 0 0 1 4 1 2 7

SURFACE

Track Profile 1m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track surface/suspended	White	1000-30-20	9 0 0 1 4 0 0 1
1-phase track surface/suspended	Black	1000-30-20	9 0 0 1 4 0 0 7

Track Profile 2m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track surface/suspended	White	2000-30-20	9 0 0 1 4 0 0 2
1-phase track surface/suspended	Black	2000-30-20	9 0 0 1 4 0 0 8

Track Profile 3m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track surface/suspended	White	3000-30-20	9 0 0 1 4 0 0 3
1-phase track surface/suspended	Black	3000-30-20	9 0 0 1 4 0 0 9



WEVER & DUCRÉ
LIGHTING

ODREY

on track 1.7 PAR16

187720GG0

End Cap

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track left/right	White	24·30·20	9 0 0 1 4 0 2 8
1-phase track left/right	Black	24·30·20	9 0 0 1 4 0 2 9

ELECTRICAL

T-Connector 1.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	145·55·20	9 0 0 1 4 0 1 0
1-phase track	Black	145·55·20	9 0 0 1 4 0 1 1

T-Connector 2.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	145·55·20	9 0 0 1 4 0 1 2
1-phase track	Black	145·55·20	9 0 0 1 4 0 1 3

T-Connector 3.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	145·55·20	9 0 0 1 4 0 1 4
1-phase track	Black	145·55·20	9 0 0 1 4 0 1 5

T-Connector 4.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	145·55·20	9 0 0 1 4 0 1 6
1-phase track	Black	145·55·20	9 0 0 1 4 0 1 7

End Feed | left

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	88·30·20	9 0 0 1 4 0 1 8
1-phase track	Black	88·30·20	9 0 0 1 4 0 1 9

End Feed | right

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	88·30·20	9 0 0 1 4 0 2 0
1-phase track	Black	88·30·20	9 0 0 1 4 0 2 1

Straight Connector

TYPE	COLOUR	L · H (MM)	ORDERCODE
1-phase track straight	White	65·17	9 0 0 1 4 0 2 2
1-phase track straight	Black	65·17	9 0 0 1 4 0 2 3

L-Connector

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track left	White	88·55·20	9 0 0 1 4 0 2 4
1-phase track left	Black	88·55·20	9 0 0 1 4 0 2 5
1-phase track right	White	88·55·20	9 0 0 1 4 0 2 6
1-phase track right	Black	88·55·20	9 0 0 1 4 0 2 7

ODREY

on track 1.7 PAR16

187720GG0

Middle Feed

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track straight	White	145 · 30 · 20	9 0 0 1 4 0 3 6
1-phase track straight	Black	145 · 30 · 20	9 0 0 1 4 0 3 7

X-Connector

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	145 · 145 · 20	9 0 0 1 4 0 4 9
1-phase track	Black	145 · 145 · 20	9 0 0 1 4 0 5 0

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	Ø50 · 60	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	Ø50 · 60	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	Ø50 · 60	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	Ø50 · 60	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	Ø50 · 60	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	Ø50 · 60	9 0 5 2 2 7 S 4