

# CENO SEMI RECESSED 1.0

176561W3

Project

Type

Notes

Quantity

Date

## GENERAL

Ceiling , Semi-Recessed

Tilt max 90°

Rotation 350°

White Matt

IP20

IC rated

Interior

Output: 500 lm

CIE flux code: 99 100 100 100 100

## LED

2700 K

CRI ≥ 90

L70 / 55000h

2 SDCM

## OPTICAL

Medium , Beam angle 31°

## ELECTRICAL

excl. driver

17 V

LED Inset 6.0 W

Class 3


350 mA

## PHYSICAL


Diameter 35 mm

Height 55 mm


0.14 kg



Semi-recessed luminaire with round base made from aluminium; surface White Matt; powder coated, matt texture; inner ring black; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; beam angle 31°; 350° rotatable and 90° tiltable; degree of protection IP20; PC3; IC rated; driver not included; light source replaceable by an authorized professional;



## LIGHT DISTRIBUTION



# CENO SEMI RECESSED 1.0

176561W3

## CONE DIAGRAM

medium 31° 350mA

| h (m) | EO° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 1440     | 0.56  |
| 2     | 360      | 1.12  |
| 3     | 160      | 1.68  |
| 4     | 90       | 2.23  |
| 5     | 60       | 2.79  |

## OPTICAL

### Honeycomb Louver

| TYPE                              | Ø (MM) | ORDERCODE       |
|-----------------------------------|--------|-----------------|
| BLIEK PETIT   CENO   LECA   PIRRO | 29     | 9 0 0 5 1 1 3 1 |

## ELECTRICAL

### Driver

| TYPE                                 | L · W · H (MM)    | VOLTAGE | ORDERCODE       |
|--------------------------------------|-------------------|---------|-----------------|
| 6W   350mA                           | 67 · 39 · 22      | 8.6-18V | 9 0 2 1 3 3 0 3 |
| 10W   350mA   1-10V dim              | 101.5 · 51 · 29.5 | 14-28V  | 9 0 2 2 3 4 0 1 |
| 10W   350mA   phase-cut dim          | 102 · 38 · 21     | 12-28V  | 9 0 2 2 3 4 0 2 |
| 15W   700mA   12-20V   phase-cut dim | 122 · 41 · 23     | 12-20V  | 9 0 2 2 5 5 0 2 |
| 14W   350mA                          | 145 · 33 · 21     | 2.5-42V | 9 0 2 4 3 5 0 1 |
| 17W   350mA   10-49V   DALI          | 108 · 52 · 22     | 10-49V  | 9 0 2 4 3 6 0 1 |