



WEVER & DUCRÉ
LIGHTING

PIRRO

OPAL on track 4.0

173484K3

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling, Track

Rotation 310°

Black Matt + Gold

IP20

Interior

Output: 685 lm

CIE flux code: 65 94 100 100 100

LED

2700 K

CRI ≥ 90

L80 / 60000h

3 SDCM

OPTICAL

Opal

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 12.0 W

Class 1

PHYSICAL

Length 182 mm

Width 50 mm

Height 65 mm


0.54 kg

75 (adapter) mm


incl. 1-phase track adapter



Downlight made from die-cast aluminium incl. 1-phase track adapter; opal PMMA cover; housing Black Matt powder coated; matt texture; with reflector in Gold wet painted; matt smooth; PCB 3-step binning; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; CRI (Colour Rendering Index) ≥ 90; 310° rotatable; degree of protection IP20; PC1; light source replaceable by an authorized professional; control gear replaceable by end-user;



LIGHT DISTRIBUTION



[173484K3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com

May 8, 2024

PIRRO

OPAL on track 4.0

173484K3

SUSPENDED

Track Adapter 1.0

TYPE	COLOUR	L · H (MM)	ORDERCODE
1-phase track	Black	85-45	9 0 0 1 4 0 4 3
1-phase track	White	85-45	9 0 0 1 4 0 4 4

Suspension Set 1.5m

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
1-phase track suspended	White	Ø29-1500	9 0 0 1 4 1 0 1
1-phase track suspended	Black	Ø29-1500	9 0 0 1 4 1 0 2

Suspension Set 3.0m

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
1-phase track suspended	White	Ø29-3000	9 0 0 1 4 1 0 3
1-phase track suspended	Black	Ø29-3000	9 0 0 1 4 1 0 4

Track Adapter 2.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	80-24-26	9 0 0 1 4 2 7 7
1-phase track	Black	80-24-26	9 0 0 1 4 2 7 8

CORNER

Adjustable Corner

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	Black	81-81-20	9 0 0 1 4 0 4 1
1-phase track	White	81-81-20	9 0 0 1 4 0 4 2

RECESSED

Mounting Bracket

TYPE	L · W · H (MM)	ORDERCODE
1-phase track recessed	35-59-35	9 0 0 1 4 1 0 0

Track Profile 1m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track recessed	White	1000-50-20	9 0 0 1 4 1 1 8
1-phase track recessed	Black	1000-50-20	9 0 0 1 4 1 1 9

PIRRO

OPAL on track 4.0

173484K3

Track Profile 2m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track recessed	White	2000-50-20	9 0 0 1 4 1 2 0
1-phase track recessed	Black	2000-50-20	9 0 0 1 4 1 2 1

Track Profile 3m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track recessed	White	3000-50-20	9 0 0 1 4 1 2 2
1-phase track recessed	Black	3000-50-20	9 0 0 1 4 1 2 3

Coverplate End Feed

TYPE	COLOUR	L · W (MM)	ORDERCODE
1-phase track recessed	White	75-50	9 0 0 1 4 1 2 4
1-phase track recessed	Black	75-50	9 0 0 1 4 1 2 5

Coverplate I/L/T/X

TYPE	COLOUR	L · W (MM)	ORDERCODE
1-phase track recessed	White	100-100	9 0 0 1 4 1 2 6
1-phase track recessed	Black	100-100	9 0 0 1 4 1 2 7

SURFACE

Track Profile 1m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track surface/suspended	White	1000-30-20	9 0 0 1 4 0 0 1
1-phase track surface/suspended	Black	1000-30-20	9 0 0 1 4 0 0 7

Track Profile 2m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track surface/suspended	White	2000-30-20	9 0 0 1 4 0 0 2
1-phase track surface/suspended	Black	2000-30-20	9 0 0 1 4 0 0 8

Track Profile 3m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track surface/suspended	White	3000-30-20	9 0 0 1 4 0 0 3
1-phase track surface/suspended	Black	3000-30-20	9 0 0 1 4 0 0 9

End Cap

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track left/right	White	24-30-20	9 0 0 1 4 0 2 8
1-phase track left/right	Black	24-30-20	9 0 0 1 4 0 2 9

PIRRO

OPAL on track 4.0

173484K3

ELECTRICAL

T-Connector 1.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	145-55-20	9 0 0 1 4 0 1 0
1-phase track	Black	145-55-20	9 0 0 1 4 0 1 1

T-Connector 2.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	145-55-20	9 0 0 1 4 0 1 2
1-phase track	Black	145-55-20	9 0 0 1 4 0 1 3

T-Connector 3.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	145-55-20	9 0 0 1 4 0 1 4
1-phase track	Black	145-55-20	9 0 0 1 4 0 1 5

T-Connector 4.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	145-55-20	9 0 0 1 4 0 1 6
1-phase track	Black	145-55-20	9 0 0 1 4 0 1 7

End Feed | left

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	88-30-20	9 0 0 1 4 0 1 8
1-phase track	Black	88-30-20	9 0 0 1 4 0 1 9

End Feed | right

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	88-30-20	9 0 0 1 4 0 2 0
1-phase track	Black	88-30-20	9 0 0 1 4 0 2 1

Straight Connector

TYPE	COLOUR	L · H (MM)	ORDERCODE
1-phase track straight	White	65-17	9 0 0 1 4 0 2 2
1-phase track straight	Black	65-17	9 0 0 1 4 0 2 3

L-Connector

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track left	White	88-55-20	9 0 0 1 4 0 2 4
1-phase track left	Black	88-55-20	9 0 0 1 4 0 2 5
1-phase track right	White	88-55-20	9 0 0 1 4 0 2 6
1-phase track right	Black	88-55-20	9 0 0 1 4 0 2 7

Middle Feed

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track straight	White	145-30-20	9 0 0 1 4 0 3 6
1-phase track straight	Black	145-30-20	9 0 0 1 4 0 3 7



WEVER & DUCRÉ
LIGHTING

PIRRO

OPAL on track 4.0

173484K3

X-Connector

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	145-145-20	9 0 0 1 4 0 4 9
1-phase track	Black	145-145-20	9 0 0 1 4 0 5 0