



WEVER & DUCRÉ
LIGHTING

PIRRO SPOT on track 2.0

173264K3

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling, Track

Rotation 310°

Black Matt + Gold

IP20

Interior

Output: 710 lm

CIE flux code: 99 100 100 100 100

LED

2700 K

CRI ≥ 90

L70 / 55000h

2 SDCM

OPTICAL

Medium, Beam angle 32°

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 11.0 W

Class 1

PHYSICAL

Length 94 mm


Width 50 mm

Height 80 mm


0.36 kg

75 (adapter) mm

incl. 1-phase track adapter



Spotlight made from die-cast aluminium incl. 1-phase track adapter; with 2 spotlights; opal PMMA cover; housing Black Matt powder coated; matt texture; with reflector in Gold wet painted; matt smooth; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; beam angle 32°; 310° rotatable; degree of protection IP20; PC1; UGR ≤ 13; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; light source replaceable by an authorized professional; control gear replaceable by end-user;




PIRRO

SPOT on track 2.0

173264K3

LIGHT DISTRIBUTION



SUSPENDED

Track Adapter 1.0

TYPE	COLOUR	L · H (MM)	ORDERCODE
1-phase track	Black	85·45	9 0 0 1 4 0 4 3
1-phase track	White	85·45	9 0 0 1 4 0 4 4

Suspension Set 1.5m

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
1-phase track suspended	White	Ø29·1500	9 0 0 1 4 1 0 1
1-phase track suspended	Black	Ø29·1500	9 0 0 1 4 1 0 2

Suspension Set 3.0m

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
1-phase track suspended	White	Ø29·3000	9 0 0 1 4 1 0 3
1-phase track suspended	Black	Ø29·3000	9 0 0 1 4 1 0 4

Track Adapter 2.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	80·24·26	9 0 0 1 4 2 7 7
1-phase track	Black	80·24·26	9 0 0 1 4 2 7 8

CORNER

Adjustable Corner

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	Black	81·81·20	9 0 0 1 4 0 4 1
1-phase track	White	81·81·20	9 0 0 1 4 0 4 2

PIRRO

SPOT on track 2.0

173264K3

RECESSED

Mounting Bracket

TYPE	L · W · H (MM)	ORDERCODE
1-phase track recessed	35 · 59 · 35	9 0 0 1 4 1 0 0

Track Profile 1m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track recessed	White	1000 · 50 · 20	9 0 0 1 4 1 1 8
1-phase track recessed	Black	1000 · 50 · 20	9 0 0 1 4 1 1 9

Track Profile 2m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track recessed	White	2000 · 50 · 20	9 0 0 1 4 1 2 0
1-phase track recessed	Black	2000 · 50 · 20	9 0 0 1 4 1 2 1

Track Profile 3m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track recessed	White	3000 · 50 · 20	9 0 0 1 4 1 2 2
1-phase track recessed	Black	3000 · 50 · 20	9 0 0 1 4 1 2 3

Coverplate End Feed

TYPE	COLOUR	L · W (MM)	ORDERCODE
1-phase track recessed	White	75 · 50	9 0 0 1 4 1 2 4
1-phase track recessed	Black	75 · 50	9 0 0 1 4 1 2 5

Coverplate I/L/T/X

TYPE	COLOUR	L · W (MM)	ORDERCODE
1-phase track recessed	White	100 · 100	9 0 0 1 4 1 2 6
1-phase track recessed	Black	100 · 100	9 0 0 1 4 1 2 7

SURFACE

Track Profile 1m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track surface/suspended	White	1000 · 30 · 20	9 0 0 1 4 0 0 1
1-phase track surface/suspended	Black	1000 · 30 · 20	9 0 0 1 4 0 0 7

Track Profile 2m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track surface/suspended	White	2000 · 30 · 20	9 0 0 1 4 0 0 2
1-phase track surface/suspended	Black	2000 · 30 · 20	9 0 0 1 4 0 0 8

PIRRO

SPOT on track 2.0

173264K3

Track Profile 3m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track surface/suspended	White	3000-30-20	9 0 0 1 4 0 0 3
1-phase track surface/suspended	Black	3000-30-20	9 0 0 1 4 0 0 9

End Cap

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track left/right	White	24-30-20	9 0 0 1 4 0 2 8
1-phase track left/right	Black	24-30-20	9 0 0 1 4 0 2 9

ELECTRICAL

T-Connector 1.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	145-55-20	9 0 0 1 4 0 1 0
1-phase track	Black	145-55-20	9 0 0 1 4 0 1 1

T-Connector 2.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	145-55-20	9 0 0 1 4 0 1 2
1-phase track	Black	145-55-20	9 0 0 1 4 0 1 3

T-Connector 3.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	145-55-20	9 0 0 1 4 0 1 4
1-phase track	Black	145-55-20	9 0 0 1 4 0 1 5

T-Connector 4.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	145-55-20	9 0 0 1 4 0 1 6
1-phase track	Black	145-55-20	9 0 0 1 4 0 1 7

End Feed | left

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	88-30-20	9 0 0 1 4 0 1 8
1-phase track	Black	88-30-20	9 0 0 1 4 0 1 9

End Feed | right

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	88-30-20	9 0 0 1 4 0 2 0
1-phase track	Black	88-30-20	9 0 0 1 4 0 2 1

Straight Connector

TYPE	COLOUR	L · H (MM)	ORDERCODE
1-phase track straight	White	65-17	9 0 0 1 4 0 2 2
1-phase track straight	Black	65-17	9 0 0 1 4 0 2 3

PIRRO

SPOT on track 2.0

173264K3

L-Connector

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track left	White	88·55·20	9 0 0 1 4 0 2 4
1-phase track left	Black	88·55·20	9 0 0 1 4 0 2 5
1-phase track right	White	88·55·20	9 0 0 1 4 0 2 6
1-phase track right	Black	88·55·20	9 0 0 1 4 0 2 7

Middle Feed

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track straight	White	145·30·20	9 0 0 1 4 0 3 6
1-phase track straight	Black	145·30·20	9 0 0 1 4 0 3 7

X-Connector

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
1-phase track	White	145·145·20	9 0 0 1 4 0 4 9
1-phase track	Black	145·145·20	9 0 0 1 4 0 5 0