



WEVER & DUCRÉ  
LIGHTING

# CENO SURFACE 4.1

176964Q5

Project

Type

Notes

Quantity

Date

## GENERAL

Ceiling , Surface

Tilt max 90°

Rotation 350°

Bronze

IP20

Interior

Output: 2130 lm

CIE flux code: 99 100 100 100 100

## LED

3000 K

CRI ≥ 90

L70 / 55000h

2 SDCM

## OPTICAL

Medium , Beam angle 31°

## ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 29.7 W

Class 1

## PHYSICAL


Diameter 34 mm

Height 55 mm

0.78 kg



Ceiling surface luminaire with 4 spotlights; made from die-cast aluminium; with rectangular base; surface Bronze; wet painted, matt smooth; inner ring black; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; beam angle 31°; 220 - 240 V; 350° rotatable and 90° tiltable; degree of protection IP20; PC1; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by an authorized professional; control gear replaceable by end-user;




CENO

SURFACE 4.1

176964Q5

LIGHT DISTRIBUTION



CONE DIAGRAM

medium 31°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 1530     | 0.56  |
| 2     | 380      | 1.12  |
| 3     | 170      | 1.68  |
| 4     | 100      | 2.23  |
| 5     | 60       | 2.79  |

OPTICAL

Honeycomb Louver

| TYPE                              | Ø (MM) | ORDERCODE       |
|-----------------------------------|--------|-----------------|
| BLIEK PETIT   CENO   LECA   PIRRO | 29     | 9 0 0 5 1 1 3 1 |