

CENO fort on track 1.0

166963B7

GENERAL

Ceiling , Track
Tilt max 90°
Rotation 360°
Black Matt
RAL 9005 ^a
IP20
Interior
Output: 3120 lm
CIE flux code: 98 100 100 100 100

LED

4000 K
CRI ≥ 90
L80 / 50000h
2 SDCM

OPTICAL

Medium , Beam angle 24°

ELECTRICAL

non dim
220 - 240 V
Total connected power 35 W
Class 2

PHYSICAL

Diameter 72 mm
Height 112 mm
0.63 kg
158 (adapter) mm
incl. 3-phase track adapter

^a Color may deviate slightly due to production conditions.


Project _____

Type _____


Notes _____

Quantity _____


Date _____



3-phase tracks spotlight made from die-cast aluminium; surface Black Matt; powder coated; matt texture; polycarbonate track adapter in Signal Black; inner ring black; spotlight head 360° rotatable and 90° tiltable; beam angle 24°; with COB (Chip on Board) technology for maximum efficiency; non dim; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; 220 - 240 V; degree of protection IP20; PC2; UGR ≤ 19; light source replaceable by an authorized professional;



LIGHT DISTRIBUTION



[166963B7] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com

CENO

fort on track 1.0

166963B7

CONE DIAGRAM

medium 24°

h (m)	EO° (lx)	ø (m)
1	12100	0.43
2	3000	0.87
3	1300	1.30
4	800	1.74
5	500	2.17

OPTICAL

Honeycomb Louver

TYPE	Ø (MM)	ORDERCODE
CENO fort on track 3 phase	61	9 0 0 5 1 1 3 2

SURFACE

Track Profile 1m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
3-phase track surface/suspended	White	1000-32-38	9 0 0 1 4 2 0 0
3-phase track surface/suspended	Black	1000-32-38	9 0 0 1 4 2 0 1

Track Profile 2m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
3-phase track surface/suspended	White	2000-32-38	9 0 0 1 4 2 0 2
3-phase track surface/suspended	Black	2000-32-38	9 0 0 1 4 2 0 3

Track Profile 3m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
3-phase track surface/suspended	White	3000-32-38	9 0 0 1 4 2 0 4
3-phase track surface/suspended	Black	3000-32-38	9 0 0 1 4 2 0 5

Flexible Connector

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
3-phase track	White	143-143-38	9 0 0 1 4 2 8 8
3-phase track	Black	143-38-31	9 0 0 1 4 2 8 9

SUSPENDED

Suspension Set 1.5m

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
3-phase track suspended	White	Ø32-1500	9 0 0 1 4 2 0 6
3-phase track suspended	Black	Ø32-1500	9 0 0 1 4 2 0 7

CENO fort on track 1.0

166963B7

Suspension Set 3.0m

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
3-phase track suspended	White	Ø32·3000	9 0 0 1 4 2 0 8
3-phase track suspended	Black	Ø32·3000	9 0 0 1 4 2 0 9

Track Adapter

TYPE	COLOUR	ORDERCODE
3-phase track	White	9 0 0 1 4 2 7 9
3-phase track	Black	9 0 0 1 4 2 8 0

Hook

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
3-phase track	White	26·28·48	9 0 0 1 4 2 8 4
3-phase track	Black	26·28·48	9 0 0 1 4 2 8 5

COVER and END CAP

End Cap

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
3-phase track left/right	White	32·32·38	9 0 0 1 4 2 1 6
3-phase track left/right	Black	32·32·38	9 0 0 1 4 2 1 7

Track Cover

TYPE	COLOUR	L · W (MM)	ORDERCODE
3-phase track 1.0 m	White	1000·26	9 0 0 1 4 2 3 6
3-phase track 1.0 m	Black	1000·26	9 0 0 1 4 2 3 7

ELECTRICAL

Cutting tool

TYPE	ORDERCODE
3-phase track and 48V track	9 0 0 1 4 1 6 5

L-Connector 1.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
3-phase track left	White	143·140·38	9 0 0 1 4 2 2 0
3-phase track left	Black	143·140·38	9 0 0 1 4 2 2 1

L-Connector 2.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
3-phase track right	White	143·140·38	9 0 0 1 4 2 2 2
3-phase track right	Black	143·140·38	9 0 0 1 4 2 2 3

Middle Feed

TYPE	COLOUR	L · H (MM)	ORDERCODE
3-phase track straight	White	253·38	9 0 0 1 4 2 2 4
3-phase track straight	Black	253·38	9 0 0 1 4 2 2 5

CENO fort on track 1.0

166963B7

Straight Connector

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
3-phase track straight	White	115-25-33	9 0 0 1 4 2 2 6
3-phase track straight	Black	115-25-33	9 0 0 1 4 2 2 7

T-Connector 1.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
3-phase track	White	254-143-38	9 0 0 1 4 2 2 8
3-phase track	Black	254-143-38	9 0 0 1 4 2 2 9

T-Connector 2.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
3-phase track	White	254-143-38	9 0 0 1 4 2 3 0
3-phase track	Black	254-143-38	9 0 0 1 4 2 3 1

T-Connector 3.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
3-phase track	White	254-143-38	9 0 0 1 4 2 3 2
3-phase track	Black	254-143-38	9 0 0 1 4 2 3 3

T-Connector 4.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
3-phase track	White	254-143-38	9 0 0 1 4 2 3 4
3-phase track	Black	254-143-38	9 0 0 1 4 2 3 5

End Feed | left

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
3-phase track	White	148-32-38	9 0 0 1 4 2 3 8
3-phase track	Black	148-32-38	9 0 0 1 4 2 3 9

End Feed | right

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
3-phase track	White	148-32-38	9 0 0 1 4 2 4 0
3-phase track	Black	148-32-38	9 0 0 1 4 2 4 1

X-Feed

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
3-phase track	White	254-254-38	9 0 0 1 4 2 4 8
3-phase track	Black	254-254-38	9 0 0 1 4 2 4 9