

MICK 1.0

159144K5

GENERAL

Ceiling , Surface
Tilt max 90°
Rotation 350°
Black Matt + Gold
RAL 9005 ^a
IP20
Interior
Output: 435 lm
CIE flux code: 90 98 100 100 100

LED

3000 K
CRI ≥ 90
L80 / 50000h
2 SDCM

OPTICAL

Medium , Beam angle 23°

ELECTRICAL

phase-cut dim
220 - 240 V
Total connected power 13.8 W
Class 1

PHYSICAL

Length 330 mm
Width 26 mm
Height 130 mm
0.35 kg

^a Color may deviate slightly due to production conditions.


Project _____

Type _____


Notes _____

Quantity _____


Date _____



Ceiling surface spotlight made from die-cast aluminium; with rectangular base; surface Black Matt + Gold; powder coated and wet painted; matt texture; RAL 9005; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; beam angle 23°; 220 - 240 V; 350° rotatable and 90° tiltable; degree of protection IP20; PC1; driver included; light source replaceable by an authorized professional; control gear replaceable by end-user;



LIGHT DISTRIBUTION



MICK
1.0

159144K5

CONE DIAGRAM

medium 18°

h (m)	EO° (lx)	ø (m)
1	2590	0.31
2	650	0.62
3	290	0.93
4	160	1.25
5	100	1.56

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.89	0.85	0.82
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to “CIE 97, Maintenance of indoor electric lighting systems”, 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.