

MICK

snooze 1.0

159643J5

GENERAL

Wall , Surface
Tilt max 90°
Rotation 350°
White Matt + Gold
IP20
Interior
Output: 200 lm
CIE flux code: 90 98 100 100 100

LED

3000 K
CRI ≥ 90
L80 / 50000 h
2 SDCM

OPTICAL

Medium , Beam angle 23°

ELECTRICAL

incl. driver
220 - 240 V
Total connected power 7.5 W
Class 1

PHYSICAL

Length 130 mm
Width 26 mm
Height 26 mm
0.39 kg
incl. switch on/off

Project _____

Type _____


Notes _____

Quantity _____


Date _____



Bedside luminaire made from die-cast aluminium with rectangular base; inclusive on/off switch in white; surface White Matt + Gold; powder coated; matt texture; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; beam angle 23°; 220 - 240 V; 350° rotatable and 90° tiltable; degree of protection IP20; PC1; driver included; light source replaceable by an authorized professional; control gear replaceable by end-user;



LIGHT DISTRIBUTION



MICK

snooze 1.0

159643J5

CONE DIAGRAM

medium 18°

h (m)	EO° (lx)	ø (m)
1	1180	0.31
2	290	0.62
3	130	0.93
4	70	1.25
5	50	1.56

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.88	0.84	0.81
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to “CIE 97, Maintenance of indoor electric lighting systems”, 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.