WEVER & DUCRÉ LIGHTING

# CHART 1.6

**752468I5**

**PROJECT**

**TYPE**

**NOTES**


**QUANTITY**

**DATE**



IP67

Square floor recessed luminaire made from stainless steel and glass; surface Inox; No matching RAL; recessed depth 185mm; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90; beam angle 38°; degree of protection IP67; Class 2; light source replaceable by Wever & Ducré or by a professional with explicit authorization;




## LUMINAIRE

Floor
Recessed
Inox
No matching RAL
IP67
IK09
Exterior
1260 lm

## LED MODULE

3000 K
CRI ≥ 90
L70 / 55000h
≤ 3 SDCM (initial MacAdam)

## OPTICAL

Medium (standard)
beam angle 38°
UGR ≤ 10
CIE flux code: 36 58 79 0 100
≥65° < 1500 cd/m²

## ELECTRICAL

phase-cut dim
220 - 240 V
system 16.1 W
Class II


## PHYSICAL

length 160 mm
width 160 mm
height 139 mm
1.45 kg

## CUTOUT

recessed depth 185 mm

## LIGHT DISTRIBUTION



## MOUNTING ACCESSORIES

**GROUND HOUSING**

| TYPE | COLOUR | VOLTAGE | Ø·H (MM) | ITEM NUMBER |
|---|---|---|---|---|
| MAP 1.6 \| CHART 1.6 \| MAP ASYM 1.6 \| CHART ASYM 1.6 | | | 213·175 | 90012204 |

['752468I5'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com