



PROJECT

TYPE

NOTES

QUANTITY


DATE



IP67



Square floor recessed luminaire made from stainless steel and glass; surface Inox; No matching RAL; recessed depth 135mm; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; beam angle 35° ; degree of protection IP67; Class 2; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Floor
Recessed
Inox
No matching RAL
IP67
IK08
Exterior
640 lm

LED MODULE

3000 K
CRI ≥ 90
L70 / 55000h
 ≤ 3 SDCM (initial MacAdam)

OPTICAL

Medium (standard)
beam angle 35°
UGR ≤ 10
CIE flux code: 23 46 70 0 100
 $\geq 65^\circ < 1500 \text{ cd/m}^2$

ELECTRICAL

phase-cut dim
220 - 240 V
system 7.9 W
Class II


PHYSICAL

length 85 mm
width 85 mm
height 120 mm
0.7 kg

CUTOUT

recessed depth 135 mm

LIGHT DISTRIBUTION





75226815



MOUNTING ACCESSORIES

GROUND HOUSING		COLOUR	VOLTAGE	Ø-H (MM)	ITEM NUMBER
TYPE					
MAP 0.9 CHART 0.9 BLINK 2.0				132-125	90012202

[75226815] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com