



WEVER & DUCRÉ
LIGHTING

MAP ASYM 1.6

7516A8I5

Project

Type

Notes

Quantity

Date

GENERAL

Floor , Recessed

Inox

IP67

IK09

Exterior

Output: 845 lm

CIE flux code: 38 67 87 0 100

LED

3000 K

CRI ≥ 90

L70 / 55000h

3 SDCM

OPTICAL

Asymetric

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 15.7 W

Class 2

PHYSICAL

Diameter 160 mm

Height 139 mm

1.72 kg

CUTOUT

Diameter 91-93 mm


Recessed depth 185 mm




IP67



Round floor recessed luminaire made from stainless steel and glass; asymmetric light beam; surface Inox; recessed depth 185 mm; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; degree of protection IP67; PC2; driver not included; light source replaceable by an authorized professional;



LIGHT DISTRIBUTION





MAP ASYM 1.6

7516A8I5

MOUNTING

Ground Housing

TYPE	Ø · H (MM)	ORDERCODE
MAP 1.6 CHART 1.6 MAP ASYM 1.6 CHART ASYM 1.6	Ø213 · 175	9 0 0 1 2 2 0 4