



PROJECT

TYPE

NOTES

QUANTITY


DATE



IP67



Round floor recessed luminaire made from stainless steel and glass; asymmetric light beam; surface Inox; recessed depth 185 mm; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; degree of protection IP67; Class 2; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Floor
Recessed
Inox
IP67
IK09
Exterior
845 lm

LED Module

3000 K
CRI ≥ 90
L70 / 55000h
 ≤ 3 SDCM (initial MacAdam)

Optical

Asymetric
CIE flux code: 38 67 87 0 100

Electrical

phase-cut dim
220 - 240 V
system 15.7 W
Class II


Physical

diameter 160 mm
height 139 mm
1.72 kg

Cutout

recessed depth 185 mm

LIGHT DISTRIBUTION





Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0	0	0	0	0
LSF	1	1	1	1	1

MF LMF × RSMF × LLMF × LSF

MF Maintenance Factor

LMF^a Luminaire Maintenance Factor

RSMF^a Room Surface Maintenance Factor

LLMF Lamp Lumens Maintenance Factor

LSF Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

MOUNTING ACCESSORIES

Ground Housing

Type	Colour	Voltage	Ø·H (MM)	Item number
MAP 1.6 CHART 1.6 MAP ASYM 1.6 CHART ASYM 1.6			213·175	90012204