

# MAP ASYM 1.2

7515A8I5

## GENERAL

Floor , Recessed

Inox

IP67

IK08

Exterior

Output: 565 lm

CIE flux code: 31 58 80 0 100

## LED

3000 K

CRI  $\geq 90$

L70 / 55000h

3 SDCM

## OPTICAL

Asymetric

## ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 11.4 W

Class 2

## PHYSICAL

Diameter 120 mm

Height 113 mm

1.06 kg

## CUTOUT

Diameter 72-74 mm

Recessed depth 160 mm

Project

Type


Notes

Quantity


Date



Round floor recessed luminaire made from stainless steel and glass; asymmetric light beam; surface Inox; recessed depth 160 mm; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; degree of protection IP67; PC2; driver not included; light source replaceable by an authorized professional;



## LIGHT DISTRIBUTION



MAP  
ASYM 1.2

7515A8I5

MOUNTING

Ground Housing

TYPE	Ø · H (MM)	ORDERCODE
MAP 1.2   CHART 1.2   MAP ASYM 1.2   CHART ASYM 1.2	Ø185 · 150	9 0 0 1 2 2 0 3