



PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Round floor recessed luminaire made from stainless steel and glass; surface Inox; No matching RAL; recessed depth 185 mm; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; beam angle 38°; degree of protection IP67; Class 2; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Floor _____

Recessed _____

Inox _____

No matching RAL _____

IP67 _____

IK09 _____

Exterior _____

1260 lm _____

LED Module

3000 K _____

CRI ≥ 90 _____

L70 / 55000h _____

≤ 3 SDCM (initial MacAdam) _____

Optical

Medium (standard) _____

beam angle 38° _____

UGR ≤ 10 _____

CIE flux code: 36 58 79 0 100 _____

$\geq 65^\circ < 1500 \text{ cd/m}^2$ _____

Electrical

phase-cut dim _____

220 - 240 V _____

system 16.1 W _____

Class II _____

Standard _____

Physical

diameter 160 mm _____

height 139 mm _____

1.43 kg _____


Cutout

recessed depth 185 mm _____

datasheet.quicksum.material

Stainless Steel 304 _____

LIGHT DISTRIBUTION





Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.92	0.84	0.76	0.69	0.63
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

MOUNTING ACCESSORIES

Ground Housing

Type	Colour	Voltage	Ø·H (MM)	Item number
MAP 1.6 CHART 1.6 MAP ASYM 1.6 CHART ASYM 1.6			213·175	90012204