



WEVER & DUCRÉ
LIGHTING

MAP 1.2

751368I5

Project

Type

Notes

Quantity

Date

GENERAL

Floor , Recessed

Inox

IP67

IK08

Exterior

Output: 995 lm

CIE flux code: 33 55 77 0 100

LED

3000 K

CRI ≥ 90

L70 / 55000h

3 SDCM

OPTICAL

Wide Flood , Beam angle 44°

UGR < 10

≥ 1500 cd/m²

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 11.9 W

Class 2

PHYSICAL

Diameter 120 mm

Height 113 mm

1.01 kg

CUTOUT

Diameter 72-74 mm


Recessed depth 120 mm




IP67



Round floor recessed luminaire made from stainless steel and glass; surface Inox; recessed depth 120 mm; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; beam angle 44°; degree of protection IP67; PC2; driver not included; light source replaceable by an authorized professional;



LIGHT DISTRIBUTION



MAP
1.2

751368I5

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.91	0.81	0.73	0.66	0.59
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF		RSMF ^a	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF ^a	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

^a According to “CIE 97, Maintenance of indoor electric lighting systems”, 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

MOUNTING

Ground Housing

TYPE	Ø · H (MM)	ORDERCODE
MAP 1.2 CHART 1.2 MAP ASYM 1.2 CHART ASYM 1.2	Ø185-150	9 0 0 1 2 2 0 3