

# MAP 0.9

751268I5

## GENERAL

Floor , Recessed  
Inox  
IP67  
IK08  
Exterior  
Output: 685 lm  
CIE flux code: 23 46 70 0 100

## LED

3000 K  
CRI  $\geq 90$   
L70 / 55000h  
3 SDCM

## OPTICAL

Flood , Beam angle 35°  
UGR < 10  
 $\geq 1500 \text{ cd/m}^2$

## ELECTRICAL

phase-cut dim  
220 - 240 V  
Total connected power 8.0 W  
Class 2

## PHYSICAL

Diameter 85 mm  
Height 120 mm  
0.7 kg

## CUTOUT

Diameter 50-52 mm  
Recessed depth 135 mm


Project \_\_\_\_\_

Type \_\_\_\_\_


Notes \_\_\_\_\_

Quantity \_\_\_\_\_


Date \_\_\_\_\_



Round floor recessed luminaire made from stainless steel and glass; surface Inox; recessed depth 135 mm; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; beam angle 35°; degree of protection IP67; PC2; driver not included; light source replaceable by an authorized professional;



## LIGHT DISTRIBUTION



MAP  
0.9

751268I5

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.94	0.88	0.83	0.77	0.72
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF		RSMF <sup>a</sup>	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF <sup>a</sup>	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

<sup>a</sup> According to “CIE 97, Maintenance of indoor electric lighting systems”, 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

MOUNTING

Ground Housing

TYPE	Ø · H (MM)	ORDERCODE
MAP 0.9   CHART 0.9	Ø132 · 125	9 0 0 1 2 2 0 2