

MAP 0.6

751168I5

GENERAL

Floor , Recessed
Inox
IP67
IK08
Exterior
Output: 310 lm
CIE flux code: 25 48 71 0 100

LED

3000 K
CRI ≥ 90
L70 / 55000h
3 SDCM

OPTICAL

Wide Flood , Beam angle 43°
UGR < 10
 $\geq 1500 \text{ cd/m}^2$

ELECTRICAL

phase-cut dim
220 - 240 V
Total connected power 5.0 W
Class 2

PHYSICAL

Diameter 55 mm
Height 95 mm
0.38 kg

CUTOUT

Diameter 38-40 mm
Recessed depth 100 mm


Project _____

Type _____


Notes _____

Quantity _____


Date _____



Round floor recessed luminaire made from stainless steel and glass; surface Inox; recessed depth 100 mm; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; beam angle 43°; degree of protection IP67; PC2; driver not included; light source replaceable by an authorized professional;



LIGHT DISTRIBUTION





MAP
0.6

751168I5

MOUNTING

Ground Housing

TYPE	Ø · H (MM)	ORDERCODE
MAP 0.6 CHART 0.6 BLINK TRIM TRIM-LESS	Ø132·105	9 0 0 1 2 2 0 1