WEVER & DUCRÉ LIGHTING

MAP 0.6

75116815

PROJECT

TYPE

NOTES

QUANTITY

DATE



IP67

Round floor recessed luminaire made from stainless steel and glass; surface Inox; No matching RAL; recessed depth 100mm; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90; beam angle 43°; degree of protection IP67; Class 2; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Floor
Recessed
Inox
No matching RAL
IP67
IK08
Exterior
310 lm

LED MODULE

3000 K
CRI ≥ 90
L70 / 55000h
≤ 3 SDCM (initial MacAdam)

OPTICAL

Wide
beam angle 43°
UGR ≤ 10
CIE flux code: 25 48 71 0 100
≥65° < 1500 cd/m²

ELECTRICAL

phase-cut dim
220 - 240 V
system 5.0 W
Class II

PHYSICAL

diameter 55 mm
height 95 mm
0.38 kg

CUTOUT

recessed depth 100 mm

LIGHT DISTRIBUTION



MOUNTING ACCESSORIES

GROUND HOUSING

TYPE	COLOUR	VOLTAGE	Ø·H (MM)	ITEM NUMBER
MAP 0.6 | CHART 0.6 | BLINK TRIM | TRIMLESS			132·105	90012201

['75116815'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com