



**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_


**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Squared wall surface mounted luminaire made from aluminium; surface Anthracite Grey; powder coated; matt texture; RAL 7016; PCB 3-step binning; phase-cut dim; light colour 3000 K;  $\leq 3$  SDCM (initial MacAdam); CRI  $\geq 90$ ; degree of protection IP65; Class 1; driver included; light source not replaceable; control gear replaceable by end-user;



**LUMINAIRE**

Wall
Surface
Anthracite Grey
RAL 7016 <sup>a</sup>
IP65
Exterior
160 lm

**LED Module**

3000 K
CRI $\geq 90$
L80 / 50000h
$\leq 3$ SDCM (initial MacAdam)

**Optical**

Asymetric
CIE flux code: 60 85 97 100
100

**Electrical**


phase-cut dim
220 - 240 V
system 5.1 W
Class I
Standard

**Physical**

length 130 mm
width 36 mm
height 130 mm
0.62 kg

<sup>a</sup> Colour may deviate slightly due to production conditions

**LIGHT DISTRIBUTION**



[7455A4A5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.