



PROJECT

TYPE

NOTES

QUANTITY


DATE



IP65



Rectangular wall recessed luminaire made from aluminium; surface Bronze; powder coated; matt texture; RAL 075 30 10; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; degree of protection IP65; Class 3; driver not included; light source not replaceable;



LUMINAIRE

Wall
Recessed
Bronze
RAL 075 30 10 ^a
IP65
Exterior
330 lm

LED MODULE

3000 K
CRI ≥ 90
L80 / 50000h
 ≤ 3 SDCM (initial MacAdam)

OPTICAL

Asymetric
CIE flux code: 58 85 97 99 100

ELECTRICAL

excl. driver
24 V
Class III


PHYSICAL

length 200 mm
width 182 mm
height 80 mm
0.41 kg

CUTOUT

length 47 mm
width 182 mm
min. ceiling thickness 12 mm
recessed depth 40 mm

LIGHT DISTRIBUTION



^a Colour may deviate slightly due to production conditions

**MOUNTING ACCESSORIES****CONCRETE HOUSING**

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
ORIS 0.7 RETO 2.0			57-55-190	90012044

RECESSED HOUSING INCL. PLASTERKIT

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
ORIS 0.7 RETO 2.0			100-67-250	90012039

ELECTRICAL ACCESSORIES**DRIVER**

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
35W 24V IP67 100-277VAC		24V	175-31-43	90212802
50W 24V IP67 100-277VAC		24V	110-63-32	90212803
100W 24V IP67 100-277VAC		24V	178-68-39	90212903
100W 24V IP67 110-240VAC		24V	153-63-32	90212904