



PROJECT

TYPE

NOTES

QUANTITY


DATE



IP65



Rectangular wall recessed luminaire made from aluminium; surface Anthracite Grey; powder coated; matt texture; RAL 7016; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; degree of protection IP65; Class 3; driver not included; light source not replaceable;



LUMINAIRE

Wall
Recessed
Anthracite Grey
RAL 7016^a
IP65
Exterior
330 lm

LED MODULE

3000 K
CRI ≥ 90
L80 / 50000h
 ≤ 3 SDCM (initial MacAdam)

OPTICAL

Asymetric
CIE flux code: 58 85 97 99 100

ELECTRICAL

excl. driver
24 V
Class III

PHYSICAL


length 200 mm
width 182 mm
height 80 mm
0.41 kg

CUTOUT

length 47 mm
width 182 mm
min. ceiling thickness 12 mm
recessed depth 40 mm

^a Colour may deviate slightly due to production conditions

LIGHT DISTRIBUTION





MOUNTING ACCESSORIES

CONCRETE HOUSING

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
ORIS 0.7 RETO 2.0			57-55-190	90012044

RECESSED HOUSING INCL. PLASTERKIT

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
ORIS 0.7 RETO 2.0			100-67-250	90012039

ELECTRICAL ACCESSORIES

DRIVER

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
35W 24V IP67 100-277VAC		24V	175-31-43	90212802
50W 24V IP67 100-277VAC		24V	110-63-32	90212803
100W 24V IP67 100-277VAC		24V	178-68-39	90212903
100W 24V IP67 110-240VAC		24V	153-63-32	90212904