



PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Square wall recessed luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; degree of protection IP65; Class 3; driver not included; light source not replaceable;



LUMINAIRE

Wall _____
 Recessed _____
 Black Matt _____
 RAL 9011 ^a _____
 IP65 _____
 Exterior _____
 170 lm _____

LED Module

3000 K _____
 CRI ≥ 90 _____
 L80 / 50000h _____
 ≤ 3 SDCM (initial MacAdam) _____

Optical

Asymetric _____
 CIE flux code: 60 86 97 99 100 _____

Electrical

excl. driver _____
 24 V _____
 Class III _____
 Standard _____

Physical

length 130 mm _____
 width 16 mm _____
 height 130 mm _____
 0.42 kg _____

Cutout


length 115 mm _____
 width 117 mm _____
 min. ceiling thickness 12 mm _____
 recessed depth 40 mm _____

datasheet.quicksum.material

Aluminium _____

^a Colour may deviate slightly due to production conditions

LIGHT DISTRIBUTION





MOUNTING ACCESSORIES

Concrete Housing

Type	Colour	Voltage	L·W·H (MM)	Item number
RETO 1.3			120-55-120	90012040

Recessed Housing incl. plasterkit

Type	Colour	Voltage	L·W·H (MM)	Item number
RETO 1.3			160-68-160	90012041

ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
35W 24V IP67		24V	175-31-43	90212802
100W 24V IP67		24V	178-68-39	90212903