



**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_


**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Square wall recessed luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K;  $\leq 3$  SDCM (initial MacAdam); CRI  $\geq 90$ ; degree of protection IP65; Class 3; driver not included; light source not replaceable;



**LUMINAIRE**

Wall \_\_\_\_\_  
 Recessed \_\_\_\_\_  
 Black Matt \_\_\_\_\_  
 RAL 9011 <sup>a</sup> \_\_\_\_\_  
 IP65 \_\_\_\_\_  
 Exterior \_\_\_\_\_  
 76 lm \_\_\_\_\_

**LED Module**

3000 K \_\_\_\_\_  
 CRI  $\geq 90$  \_\_\_\_\_  
 L80 / 50000h \_\_\_\_\_  
 $\leq 3$  SDCM (initial MacAdam) \_\_\_\_\_

**Optical**

Asymetric \_\_\_\_\_  
 CIE flux code: 64 88 98 99 100 \_\_\_\_\_

**Electrical**

excl. driver \_\_\_\_\_  
 24 V \_\_\_\_\_  
 Class III \_\_\_\_\_  
 Standard \_\_\_\_\_

**Physical**

length 80 mm \_\_\_\_\_  
 width 16 mm \_\_\_\_\_  
 height 80 mm \_\_\_\_\_  
 0.24 kg \_\_\_\_\_

**Cutout**


length 66 mm \_\_\_\_\_  
 width 66 mm \_\_\_\_\_  
 min. ceiling thickness 12 mm \_\_\_\_\_  
 recessed depth 40 mm \_\_\_\_\_

**datasheet.quicksum.material**

Aluminium \_\_\_\_\_

<sup>a</sup> Colour may deviate slightly due to production conditions

**LIGHT DISTRIBUTION**





**MOUNTING ACCESSORIES**

**Concrete Housing**

Type	Colour	Voltage	L·W·H (MM)	Item number
RETO 0.8			69-69-61	90012046

**Recessed Housing incl. plasterkit**

Type	Colour	Voltage	L·W·H (MM)	Item number
RETO 0.8			109-109-74	90012047

**ELECTRICAL ACCESSORIES**

**Driver**

Type	Colour	Voltage	L·W·H (MM)	Item number
35W   24V   IP67			175-31-43	90212802
100W   24V   IP67			178-68-39	90212903