



PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Floor surface mounted luminaire made from die-cast aluminium; surface Bronze; powder coated; matt texture; RAL 075 30 10; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; CRI ≥ 90; 220 - 240 V; degree of protection IP65; Class I; optional ground spike available; fixation base not included; light source not replaceable;



LUMINAIRE

Floor
Standing
Bronze
RAL 075 30 10 ^a
IP65
Exterior
215 lm

LED Module

3000 K
CRI ≥ 90
L70 / 50000h
≤ 3 SDCM (initial MacAdam)

Optical

Asymetric
CIE flux code: 51 89 97 98 100

Electrical

phase-cut dim
220 - 240 V
system 6.9 W
Class I
Standard

Physical


length 70 mm
width 70 mm
height 150 mm
0.69 kg

datasheet.quicksum.material

Aluminium

^a Colour may deviate slightly due to production conditions

LIGHT DISTRIBUTION





BASE

Concrete Ground Fixation

Type	Colour	Voltage	L·W·H (MM)	Item number
LINUS			112-112-359	90013302

Ground Spike

Type	Colour	Voltage	L·W·H (MM)	Item number
LINUS			112-112-357	90013103

Pole 150

Type	Colour	Voltage	L·W·H (MM)	Item number
LINUS	Anthracite Grey		112-112-150	910024A0
LINUS	Dark Grey Texture		112-112-150	910024D0
LINUS	Bronze		112-112-150	910024Q0

Pole 350

Type	Colour	Voltage	L·W·H (MM)	Item number
LINUS	Anthracite Grey		112-112-350	910026A0
LINUS	Dark Grey Texture		112-112-350	910026D0
LINUS	Bronze		112-112-350	910026Q0

Pole 550

Type	Colour	Voltage	L·W·H (MM)	Item number
LINUS	Anthracite Grey		112-112-550	910028A0
LINUS	Dark Grey Texture		112-112-550	910028D0
LINUS	Bronze		112-112-550	910028Q0