



**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_


**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Rectangular wall recessed luminaire made from aluminium; surface Bronze; powder coated; matt texture; RAL 075 30 10; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90; degree of protection IP65; Class 3; driver not included; light source not replaceable;



**LUMINAIRE**

Wall
Recessed
Bronze
RAL 075 30 10 <sup>a</sup>
IP65
Exterior
70 / 100 lm

**LED Module**

3000 K
CRI ≥ 90
L70 / 60000h
≤ 3 SDCM (initial MacAdam)

**Optical**

Asymmetric
CIE flux code: 44 78 91 84 100

**Electrical**

excl. driver
9 V
Class III
Standard

**Physical**

length 130 mm
width 341 mm
height 130 mm
0.34 kg

**Cutout**



length 115 mm
width 117 mm
min. ceiling thickness 12 mm
recessed depth 40 mm

**datasheet.quicksum.material**

Aluminium
-----------

<sup>a</sup> Colour may deviate slightly due to production conditions

**LIGHT DISTRIBUTION**





## MOUNTING ACCESSORIES

### Concrete Housing

Type	Colour	Voltage	L·W·H (MM)	Item number
RETO 1.3			120-55-120	90012040

### Recessed Housing incl. plasterkit

Type	Colour	Voltage	L·W·H (MM)	Item number
RETO 1.3			160-68-160	90012041

## ELECTRICAL ACCESSORIES

### Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
3W   350 mA   3-15V   IP66		3-15V	52-30-23	90213101
7W   500mA   5-14.5V   IP67		5-14.5V	57-41-24	90214301
7W   700mA   3-10.5V   IP67		3-10,5V	57-41-24	90215301