



PROJECT

TYPE

NOTES

QUANTITY


DATE



IP65



Rectangular wall recessed luminaire made from aluminium; surface Anthracite Grey; powder coated; matt texture; RAL 7016; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; degree of protection IP65; Class 3; driver not included; light source not replaceable;



LUMINAIRE

Wall
Recessed
Anthracite Grey
RAL 7016 ^a
IP65
Exterior
70 / 100 lm

LED Module

3000 K
CRI ≥ 90
L70 / 60000h
 ≤ 3 SDCM (initial MacAdam)

Optical

Asymmetric
CIE flux code: 44 78 91 84 100

Electrical

excl. driver
9 V
Class III

Physical



length 130 mm
width 341 mm
height 130 mm
0.34 kg

Cutout

length 115 mm
width 117 mm
min. ceiling thickness 12 mm
recessed depth 40 mm

^a Colour may deviate slightly due to production conditions

LIGHT DISTRIBUTION





MOUNTING ACCESSORIES

Concrete Housing

Type	Colour	Voltage	L·W·H (MM)	Item number
ORIS 1.3 RETO 1.3			120-55-120	90012040

Recessed Housing incl. plasterkit

Type	Colour	Voltage	L·W·H (MM)	Item number
ORIS 1.3 RETO 1.3			160-68-160	90012041

ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
3W 350 mA 3-15V IP66		3-15V	52-30-23	90213101
7W 500mA 5-14.5V IP67		5-14.5V	57-41-24	90214301
7W 700mA 3-10.5V IP67		3-10,5V	57-41-24	90215301