



PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Rectangular wall recessed luminaire made from aluminium; surface Anthracite Grey; powder coated; matt texture; RAL 7016; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; degree of protection IP65; Class 3; driver not included; light source not replaceable;



LUMINAIRE

Wall _____

Recessed _____

Anthracite Grey _____

RAL 7016 ^a _____

IP65 _____

Exterior _____

70 lm / 350mA _____

100 lm / 700mA _____

LED Module

3000 K _____

CRI ≥ 90 _____

L70 / 60000h _____

≤ 3 SDCM (initial MacAdam) _____

70 lm / 350mA _____

23 lm/W ^b _____

3.1 W ^b _____

Optical

Asymmetric _____

CIE flux code: 44 78 91 84 100 _____

Electrical

excl. driver _____

9 V _____

Class III _____

Standard _____

Physical

length 130 mm _____

width 341 mm _____

height 130 mm _____

0.34 kg _____

Cutout

length 115 mm _____

width 117 mm _____

min. ceiling thickness 12 mm _____



recessed depth 40 mm _____

datasheet.quicksum.material

Aluminum _____

^a Colour may deviate slightly due to production conditions
^b Without electrical and optical losses

LIGHT DISTRIBUTION





MOUNTING ACCESSORIES

Concrete Housing

Type	Colour	Voltage	L·W·H (MM)	Item number
RETO 1.3			120-55-120	90012040

Recessed Housing incl. plasterkit

Type	Colour	Voltage	L·W·H (MM)	Item number
RETO 1.3			160-68-160	90012041

ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
3W 350 mA 3-15V IP66		3-15V	52-30-23	90213101
7W 500mA 5-14.5V IP67		5-14.5V	57-41-24	90214301
7W 700mA 3-10.5V IP67		3-10.5V	57-41-24	90215301