




PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Rectangular wall recessed luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; degree of protection IP65; Class 3; driver not included; light source not replaceable;



LUMINAIRE

Wall _____

Recessed _____

Black Matt _____

RAL 9011 ^a _____

IP65 _____

Exterior _____

75 lm / 700mA _____

44 lm / 350mA _____

LED Module

3000 K _____

CRI ≥ 90 _____

L70 / 60000h _____

≤ 3 SDCM (initial MacAdam) _____

44 lm / 350mA _____

22 lm/W ^b _____

2 W ^b _____

Optical

Asymetric _____

CIE flux code: 41 77 91 85 100 _____

Electrical

excl. driver _____

6 V _____

Class III _____

Standard _____

Physical

length 80 mm _____

width 33 mm _____

height 80 mm _____

0.16 kg _____

Cutout

length 66 mm _____

width 66 mm _____

min. ceiling thickness 12 mm _____



recessed depth 40 mm _____

datasheet.quicksum.material

Aluminium _____

^a Colour may deviate slightly due to production conditions
^b Without electrical and optical losses

LIGHT DISTRIBUTION



7094A1B5


MOUNTING ACCESSORIES

Concrete Housing

Type	Colour	Voltage	L·W·H (MM)	Item number
RETO 0.8			69-69-61	90012046

Recessed Housing incl. plasterkit

Type	Colour	Voltage	L·W·H (MM)	Item number
RETO 0.8			109-109-74	90012047

ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
3W 350 mA 3-15V IP66		3-15V	52-30-23	90213101
7W 500mA 5-14.5V IP67		5-14.5V	57-41-24	90214301
7W 700mA 3-10.5V IP67		3-10,5V	57-41-24	90215301