



PROJECT

TYPE


NOTES

QUANTITY

DATE



Round outdoor floor or wall projector; surface Bronze; powder coated; matt texture; RAL 075 30 10; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 80 ; 220 - 240 V; 110° tiltable; beam angle 100°; degree of protection IP65; Class 2; driver included; optional ground spike available; optional snoot in Black Matt available; light source not replaceable; control gear replaceable by end-user;



LUMINAIRE

Floor
Standing
tilt max 110 °
Bronze
RAL 075 30 10 ^a
IP65
Exterior
1520 lm

LED Module

3000 K
CRI ≥ 80
L80 / 60000h
 ≤ 3 SDCM (initial MacAdam)

Optical

Extreme wide
beam angle 100°
UGR ≤ 10
CIE flux code: 0 0 0 0 100
 $\geq 65^\circ < 1500 \text{ cd/m}^2$

Electrical

phase-cut dim
220 - 240 V
system 23.7 W
Class II
Standard

Physical


diameter 160 mm
height 35 mm
1.41 kg

datasheet.quicksum.material

Aluminium

^a Colour may deviate slightly due to production conditions

LIGHT DISTRIBUTION





BASE

Ground Spike

Type	Colour	Voltage	Ø-H (MM)	Item number
X-BEAM			43-212	90013115

OPTICAL ACCESSORIES

Snoot round

Type	Colour	Voltage	Ø-W (MM)	Item number
X-BEAM	Black		166-45	90019031