



PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Round outdoor floor or wall projector; surface Black Matt; powder coated; matt texture; RAL 9011; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 80 ; 220 - 240 V; 110° tiltable; beam angle 100°; degree of protection IP65; Class 2; driver included; optional ground spike available; optional snoot in Black Matt available; light source not replaceable; control gear replaceable by end-user;



LUMINAIRE

Floor _____
 Standing _____
 tilt max 110 ° _____
 Black Matt _____
 RAL 9011^a _____
 IP65 _____
 Exterior _____
 1520 lm _____

LED Module

3000 K _____
 CRI ≥ 80 _____
 L80 / 60000h _____
 ≤ 3 SDCM (initial MacAdam) _____

Optical

Extreme wide _____
 beam angle 100° _____
 UGR ≤ 10 _____
 CIE flux code: 0 0 0 0 100 _____
 $\geq 65^\circ < 1500 \text{ cd/m}^2$ _____

Electrical

phase-cut dim _____
 220 - 240 V _____
 system 23.7 W _____
 Class II _____
 Standard _____

Physical


diameter 160 mm _____
 height 35 mm _____
 1.41 kg _____

datasheet.quicksum.material

Aluminium _____

^a Colour may deviate slightly due to production conditions

LIGHT DISTRIBUTION



[700474B4] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

700474B4



BASE

Ground Spike

Type	Colour	Voltage	Ø-H (MM)	Item number
X-BEAM			43-212	90013115

OPTICAL ACCESSORIES

Snoot round

Type	Colour	Voltage	Ø-W (MM)	Item number
X-BEAM	Black		166-45	90019031