



**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_


**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Round outdoor floor or wall projector; surface Anthracite Grey; powder coated; matt texture; RAL 7016; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K;  $\leq 3$  SDCM (initial MacAdam); CRI  $\geq 80$ ; 220 - 240 V; 110° tiltable; beam angle 100°; degree of protection IP65; Class 2; driver included; optional ground spike available; optional snoot in Black Matt available; light source not replaceable; control gear replaceable by end-user;



**LUMINAIRE**

Floor \_\_\_\_\_  
 Standing \_\_\_\_\_  
 tilt max 110 ° \_\_\_\_\_  
 Anthracite Grey \_\_\_\_\_  
 RAL 7016 <sup>a</sup> \_\_\_\_\_  
 IP65 \_\_\_\_\_  
 Exterior \_\_\_\_\_  
 1520 lm \_\_\_\_\_

**LED Module**

3000 K \_\_\_\_\_  
 CRI  $\geq 80$  \_\_\_\_\_  
 L80 / 60000h \_\_\_\_\_  
 $\leq 3$  SDCM (initial MacAdam) \_\_\_\_\_

**Optical**

Extreme wide \_\_\_\_\_  
 beam angle 100° \_\_\_\_\_  
 UGR  $\leq 10$  \_\_\_\_\_  
 CIE flux code: 0 0 0 0 100 \_\_\_\_\_  
 $\geq 65^\circ < 1500$  cd/m<sup>2</sup> \_\_\_\_\_

**Electrical**

phase-cut dim \_\_\_\_\_  
 220 - 240 V \_\_\_\_\_  
 system 23.7 W \_\_\_\_\_  
 Class II \_\_\_\_\_  
 Standard \_\_\_\_\_

**Physical**


diameter 160 mm \_\_\_\_\_  
 height 35 mm \_\_\_\_\_  
 1.41 kg \_\_\_\_\_

**datasheet.quicksum.material**

Aluminum \_\_\_\_\_

<sup>a</sup> Colour may deviate slightly due to production conditions

**LIGHT DISTRIBUTION**



700474A4



## BASE

### Ground Spike

Type	Colour	Voltage	Ø-H (MM)	Item number
X-BEAM			43-212	90013115

## OPTICAL ACCESSORIES

### Snoot round

Type	Colour	Voltage	Ø-W (MM)	Item number
X-BEAM	Black		166-45	90019031