




PROJECT

TYPE

NOTES

QUANTITY

DATE



Cylindrical wall surface mounted luminaire made from aluminium; surface Champagne Brushed; No matching RAL; direct/indirect light distribution; PCB 3-step binning; phase-cut dim; light colour 1800 - 2850 K colour warm dimming; CRI \geq 90; 220 - 240 V; degree of protection IP20; Class 1; driver included; inclusive flaps for adjustable beam angle; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

LUMINAIRE

Wall _____
 Surface _____
 Champagne Brushed _____
 No matching RAL _____
 IP20 _____
 Interior _____
 total 820 lm _____

LED Module

colour warm dimming _____
 1800 - 2850 K _____
 CRI \geq 90 _____
 L80 / 55000h _____
 \leq 3 SDCM (initial MacAdam) _____

Optical

Variable _____

Electrical


phase-cut dim _____
 220 - 240 V _____
 system 11.0 W _____
 Class I _____
 Standard _____

Physical

diameter 150 mm _____
 height 100 mm _____
 0.69 kg _____

datasheet.quicksum.material

Aluminium _____



[‘342148M9’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.