




**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_


**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Cylindrical wall surface mounted luminaire made from aluminium; surface Champagne; wet painted; brushed; No matching RAL; direct/indirect light distribution; PCB 3-step binning; phase-cut dim; light colour 1800 - 2850 K colour warm dimming; CRI ≥ 90; 220 - 240 V; degree of protection IP20; Class I; driver included; inclusive flaps for adjustable beam angle; light source replaceable by an authorized professional;



**LUMINAIRE**

Wall \_\_\_\_\_  
 Surface \_\_\_\_\_  
 Champagne \_\_\_\_\_  
 No matching RAL \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_  
 total 620 lm \_\_\_\_\_

**LED Module**

colour warm dimming \_\_\_\_\_  
 1800 - 2850 K \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_  
 L80 / 55000h \_\_\_\_\_  
 ≤ 3 SDCM (initial MacAdam) \_\_\_\_\_

**Optical**

Variable \_\_\_\_\_

**Electrical**

phase-cut dim \_\_\_\_\_  
 220 - 240 V \_\_\_\_\_  
 system 11.0 W \_\_\_\_\_  
 Class I \_\_\_\_\_  
 Standard \_\_\_\_\_

**Physical**

diameter 150 mm \_\_\_\_\_  
 height 160 mm \_\_\_\_\_  
 0.85 kg \_\_\_\_\_

**datasheet.quicksum.material**

Aluminium \_\_\_\_\_