



PROJECT

TYPE


NOTES

QUANTITY

DATE



Wall surface luminaire made from die-cast aluminium; surface White Matt; powder coated, matt texture; RAL 9010; up and down light emission; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90 ; beam angle 31°; degree of protection IP20; Class I; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



LUMINAIRE

Wall
 Surface
 White Matt
 RAL 9010 ^a
 IP20
 Interior
 545 lm


LED Module

3000 K
 CRI ≥ 90
 L70 / 55000h
 ≤ 2 SDCM (initial MacAdam)

Optical

Medium (standard)
 beam angle 31°
 UGR ≤ 13
 CIE flux code: 98 100 100 50
 100
 $\geq 65^\circ < 1500$ cd/m²

LIGHT DISTRIBUTION



Electrical

phase-cut dim
 220 - 240 V
 system 7.7 W
 Class I
 Standard

Physical

diameter 35 mm
 height 120 mm
 0.28 kg

datasheet.quicksum.material

Aluminium

^a Colour may deviate slightly due to production conditions

376264W5



OPTICAL ACCESSORIES

Honeycomb Louver

Type

BLIEK petit | CENO | LECA | PIRRO | QITO

Colour

Black

Voltage

Ø (MM)

29

Item number

915230B0