




PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Cylindrical wall surface mounted luminaire made from aluminium; surface Champagne Brushed; No matching RAL; direct light distribution; PCB 3-step binning; phase-cut dim; light colour 3000 K; CRI ≥ 90; 220 - 240 V; degree of protection IP20; Class I; inclusive flaps for adjustable beam angle; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Wall _____

Surface _____

Champagne Brushed _____

No matching RAL _____

IP20 _____

Interior _____

370 lm _____

LED Module

3000 K _____

CRI ≥ 90 _____

L80 / 55000h _____

≤ 3 SDCM (initial MacAdam) _____

Optical

Variable _____

Electrical

phase-cut dim _____

220 - 240 V _____

system 6.0 W _____

Class I _____

Standard _____

Physical

diameter 150 mm _____

height 100 mm _____

0.62 kg _____

datasheet.quicksum.material

Aluminium _____

[‘342168M5’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.