




PROJECT

TYPE


NOTES

QUANTITY

DATE



Wall surface luminaire made from aluminium; surface White Matt; powder coated; matt texture; RAL 9010; PCB 3-step binning; phase-cut dim; light colour 2700 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 80 ; 220 - 240 V; degree of protection IP20; Class 1; driver included; light source not replaceable; control gear replaceable by end-user;



LUMINAIRE

Wall
 Surface
 White Matt
 RAL 9010 ^a
 IP20
 Interior
 1190 lm

LED Module

2700 K
 CRI ≥ 80
 L80 / 60000h
 ≤ 3 SDCM (initial MacAdam)

Optical

Asymetric
 CIE flux code: 37 64 82 0 100

Electrical

phase-cut dim
 220 - 240 V
 system 13.7 W
 Class I
 Standard

Physical


length 180 mm
 width 78 mm
 height 30 mm
 0.69 kg

datasheet.quicksum.material

Aluminium

^a Colour may deviate slightly due to production conditions

LIGHT DISTRIBUTION



[‘3371A4W2’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.