



PROJECT

TYPE


NOTES

QUANTITY

DATE



Tubular wall surface luminaire made from aluminium; surface Black Matt + Champagne; powder coated; matt texture + wet painted; smooth semi glossy; RAL 9011 + No matching RAL; up and down light emission; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90 ; beam angle 23°; 220 - 240 V; degree of protection IP20; Class I; UGR ≤ 10 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



LUMINAIRE

Wall

Surface

Black Matt + Champagne

RAL 9011 + No matching RAL ^a

IP20

Interior

indirect 840 lm

direct 840 lm

total 1680 lm

LED Module

3000 K

CRI ≥ 90

L80 / 50000h

≤ 2 SDCM (initial MacAdam)

Optical

Medium (standard)

beam angle 23°

CIE flux code: 100 100 100 52

100

Electrical

phase-cut dim

220 - 240 V

system 22.8 W

Class I

Standard

Physical

length 71 mm

width 47 mm

height 720 mm


0.96 kg

datasheet.quicksum.material

Aluminium

^a Colour may deviate slightly due to production conditions

LIGHT DISTRIBUTION



[‘333464CH5’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.