



**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_

**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



**LUMINAIRE**

Wall
Surface
Black Matt
RAL 9011 <sup>a</sup>
IP20
Interior
indirect 795 lm
direct 795 lm
total 1590 lm


**LED Module**

2700 K
CRI ≥ 90
L80 / 50000h
≤ 2 SDCM (initial MacAdam)

**Optical**

Medium (standard)
beam angle 23°
CIE flux code: 100 100 100 52 100

**LIGHT DISTRIBUTION**



Tubular wall surface luminaire made from aluminium; surface Black Matt; powder coated, matt texture; RAL 9011; up and down light emission; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90; beam angle 23°; 220 - 240 V; degree of protection IP20; Class 1; UGR ≤ 10; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m<sup>2</sup>; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

**Electrical**

phase-cut dim
220 - 240 V
system 22.8 W
Class I
Standard

**Physical**

length 71 mm
width 47 mm
height 720 mm
0.96 kg

**datasheet.quicksum.material**

Aluminium

<sup>a</sup> Colour may deviate slightly due to production conditions

