



PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Rectangular wall recessed luminaire made from aluminium; surface White Matt; powder coated; matt texture; RAL 9010; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; degree of protection IP20; Class 3; driver not included; light source not replaceable;



LUMINAIRE

Wall _____
 Recessed _____
 White Matt _____
 RAL 9010 ^a _____
 IP20 _____
 Interior _____
 150 lm / 700mA _____
 90 lm / 350mA _____

LED Module

3000 K _____
 CRI ≥ 90 _____
 L70 / 60000h _____
 ≤ 3 SDCM (initial MacAdam) _____
 90 lm / 350mA _____
 45 lm/W ^b _____
 2 W ^b _____

Optical

Asymmetric _____
 CIE flux code: 41 77 91 85 100 _____

Electrical

excl. driver _____
 6 V _____
 Class III _____

Physical



length 80 mm _____
 width 33 mm _____
 height 80 mm _____
 0.15 kg _____

Cutout

length 66 mm _____
 width 66 mm _____
 min. ceiling thickness 12 mm _____
 recessed depth 40 mm _____

^a Colour may deviate slightly due to production conditions
^b Without electrical and optical losses

LIGHT DISTRIBUTION



3274A1W5



MOUNTING ACCESSORIES

Concrete Housing

Type	Colour	Voltage	L·W·H (MM)	Item number
ORIS 0.8 RETO 0.8			69-69-61	90012046

Recessed Housing incl. plasterkit

Type	Colour	Voltage	L·W·H (MM)	Item number
ORIS 0.8 RETO 0.8			109-109-74	90012047

ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
6W 350mA 3-22V		3-22V	68-35-21	90213202
6W 700mA 3-8.4V		3-8,4V	68-35-21	90215203

[3274A1W5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.